



CONVENTIONAL



PLATINUM



COILOVER



XT BARREL



OFF ROAD



BUMP STOP

MOTORSPORT CATALOG 2013

Audi Sport
Official Supplier



THE WILL TO WIN

DOMINATE THE TRACK.

For more than 60 years, Eibach has dedicated itself to one simple quest: building the finest suspension components in the world. The inspiration for this effort can be summed up in four words: The Will To Win. And the results are showcased every day in the demanding world of racing, from the legendary Formula 1 circuits and rugged WRC stages around the world, to the high-banked ovals and dirt tracks of America. From Europe's Monza, Silverstone, Nurburgring and LeMans, to Australia's V8 Supercar tracks and to the fast-growing racing series in Asia.

As the stakes in racing grow ever higher, competition gets even tougher. Precision, reliability and repeatability assume greater importance, as preparation for winning race efforts becomes more crucial than ever. And Eibach suspension components, which ultimately determine handling, balance and overall performance, must be nothing less than perfect.

CONTENT

Application Guide	5
Eibach Race Spring Systems	6
Eibach Accessories	7-10
Applications	11-42



EIBACH SPRINGS | Quality Unsurpassed

Performance Perfected

- Ultra-Lightweight for Reduced Unsprung Mass
- Maximum Travel in Combination with Smallest Block Heights
- Exceptional Block Resistance and Durability
- Precision Tolerances—The Tightest in the Industry
- Precision Planparallel and Square End Configurations Under Unloaded and Loaded Conditions to +/- 1 Degree
- Lowest Side Loads with Load Center Ideally Located Relative to Spring Axis
- Highest Linearity and Guaranteed Rate Consistency Within 2% Of Advertised Rate
- Each Spring Individually Tested and Rated
- Eibach Springs Lifetime Warranty

Eibach produces the finest racecar springs in the world. Period. When other springs sag, or need frequent replacement, top race teams, from F1 to WRC, from Le Mans to NASCAR, inevitably turn

to Eibach. And, also inevitably, wonder why they didn't choose Eibach in the first place.

To produce springs with unparalleled precision and repeatability, Eibach uses the world's finest Hi-Ten spring steel, produced to exceedingly precise tolerances—according to Eibach specs.

We use world-renowned German CNC coilers, as well as many machines engineered and built specifically by Eibach. In short, we use state-of-the-art technology, in every step of the manufacturing process.

But it's not just about machines and technology: it's about people. Most notably, the Eibach Springmeisters, working at production plants in Germany and the USA: Talented, expert craftsmen, each committed to creating the finest race springs in the world.

APPLICATIONS

	Springs	Tender	Helper	Coupler	Adapter	Isolator	Torsion Release Bearing	Locator	Coil Sleeve	Spring Bag	PAGE
COILOVER											
1.63" I.D. (QUARTER MIDGET)											11
1.88" I.D.											11-12
2.00" I.D.											12-13
2.25" I.D.											13-17
2.50" I.D. ELITE SERIES											17-18
2.50" I.D. XT BARREL											18-19
2.50" I.D.											19-24
3.00" I.D.											24-26
3.75" I.D.											26-27
60MM I.D.											36-39
70MM I.D.											40-41
36MM I.D. (F3 / C SPRINGS)											42
CONVENTIONAL FRONT SPRINGS											
8.75" / 5.75" O.D.											28-29
9.50" / 5.00" O.D.											29
9.50" / 5.50" O.D.											29-30
10.50" / 5.50" O.D.											30
PLATINUM SPRINGS											
REAR (ER)											30-32
MAXIMUM LOAD REAR											31-32
CONVENTIONAL REAR SPRINGS											
LOADED HEIGHT (NASCAR SPECS)											32-33
11.00" O.D.											33
13.00" O.D.											33-34
15.00" O.D.											34
16.00" O.D.											34
PULL BAR											
											35
BUMPSTOPS											
											10
LOCKER SPRINGS											
											10

EIBACH RACE SPRING SYSTEMS

Eibach Double-Spring System

Suspension tuning is a precise balance. On one hand, the spring system should be soft enough to absorb track irregularities assuring maximum adhesion, while on the other hand the spring system must be firm enough to reduce the body roll, squat, and dive of the vehicle during cornering, acceleration and braking. For optimum balance, Eibach has developed the ERS double-spring system. By combining Eibach Main, Tender and/or Helper springs, the suspension engineer or weekend racer can create the perfect combination of spring rates for the ultimate suspension set-up. With our extensive range of motorsport spring sizes and rates—our ERS double-spring system is unsurpassed in performance and flexibility. For Off-Road racing where extreme wheel travel is a must—combining two different rate main springs gives you the softer rate required for small bumps and a stiffer final rate to prevent bottoming on the bigger bumps and jumps.



Eibach Main And Tender System

The Eibach Main and Tender spring concept provides a softer initial rate when both springs are compressed together, then delivers the desired firmer final rate once the tender spring closes completely. The Main spring has a linear-rate characteristic and determines the final rate of the system. The Tender springs are available in linear or progressive-rate (shown) and determine the initial rate of the spring-system.



Eibach Main And Helper System

A Helper spring is used to prevent the Main spring from becoming loose in the spring seat when the suspension is unloaded or at full droop. The Helper spring, unlike the Tender spring, has very little spring rate, and therefore has no effect on the suspension characteristics of the vehicle. Up to 2" (50mm) of spring-to-perch gap can be covered with the use of a Helper spring.



EIBACH ACCESSORIES

SPRING BAGS | Keep the Dirt Out

- Made from Lightweight Material
- Eliminates Mud Packing Inside Coils
- Keeps Spring Adjuster and Damper Shaft Clean-Extends Damper Life
- Reinforced Wear Bars for Long Life
- Washable Material
- Easily Opened for Shock & Spring Adjustment



Part Number	Quantity	Spring Diameter		Spring Length	
		inch	mm	inch	mm
SPRING BAGS (Nylon)					
New! ESB12.188	2	1.88	48	10" - 12"	254-305
New! ESB12.225	2	2.25	57	10" - 12"	254-305
ESB10.250	2	2.50	64	8" - 10"	203-254
ESB12.250	2	2.50	64	10" - 12"	254-305
ESB14.250	2	2.50	64	12" - 14"	305-356
ESB16.250	2	2.50	64	14" - 16"	356-406
ESB12.300 (Fits XT Barrel Springs)	2	2.50-3.00	64-76	10" - 12"	254-305
ESB14.300 (Fits XT Barrel Springs)	2	2.50-3.00	64-76	12" - 14"	305-356
ESB16.300 (Fits XT Barrel Springs)	2	2.50-3.00	64-76	14" - 16"	356-406
ESB12.300	2	3.00	76	10" - 12"	254-305
ESB14.300	2	3.00	76	12" - 14"	305-356
ESB16.300	2	3.00	76	14" - 16"	356-406
ESB14.500	2	5.00	127	12" - 14"	305-356
ESB16.500	2	5.00	127	14" - 16"	356-406
New! ESB875.500 (Fits Pull Bar Springs)	1	5.00	127	8.75"	222
New! ESB5.400 (Fits 6th Coil Springs)	1	5.00	127	4"	102
SPRING BAGS (Neoprene)					
New! ESBN18.250	2	2.50	64	18" - 20"	457-508
New! ESBN20.250	2	2.50	64	20" - 22"	508-559
New! ESBN22.250	2	2.50	64	22" - 24"	559-610
New! ESBN26.250	2	2.50	64	26" - 28"	660-711
New! ESBN30.250	2	2.50	64	30" - 32"	762-813
New! ESBN20.300	2	3.00	76	20" - 22"	508-559
New! ESBN22.300	2	3.00	76	22" - 24"	559-610

EIBACH ACCESSORIES

COIL SLEEVE | Critical Spring Tuning

- Eliminate Frame Drag while using Softer Spring Rates
- Allows Critical Travel Adjustability without Rate Change
- Spring Stays Linear
- Durable—Will Withstand 2500LBS of Load
- Includes Adhesive Strip to Stay in Place



Part Number	Quantity	Spring Diameter Range		Spring Wire Diameter Range		Coil Sleeve Length	
		inch	mm	inch	mm	inch	mm
Coil Sleeve							
CS3001	1	2.50-3.50	64-89	0.423-0.541	10.75-13.75	10.31	262
CS3002	1	2.50-3.50	64-89	0.551-0.650	14.00-16.50	10.31	262
CS5001 (NASCAR Approved)	1	4.50-6.00	114-152	0.423-0.541	10.75-13.75	13.43	341
CS5001L	1	4.50-6.00	114-152	0.423-0.541	10.75-13.75	16.50	419
CS5002 (NASCAR Approved)	1	4.50-6.00	114-152	0.551-0.650	14.00-16.50	13.43	341
CS5002L	1	4.50-6.00	114-152	0.551-0.650	14.00-16.50	16.50	419

SPRING LOCATORS | Precision Fitment

- Lightweight and Durable Aluminum Design
- CNC Precision Machined for Accuracy
- Maintains Critical Spring Fitment
- Eliminates Spring Movement



Part Number	Quantity	Inside Diameter (Perch O.D.)		Outside Diameter (Spring I.D.)	
		inch	mm	inch	mm
Spring Locator					
ESL350.4125	1	3.50	89	4.125	105
ESL350.4188	1	3.50	89	4.188	106
ESL375.4000	1	3.75	95	4.000	102
ELS375.4063	1	3.75	95	4.063	103
ESL375.4125	1	3.75	95	4.125	105
ESL375.4188	1	3.75	95	4.188	106
ESL375.4313	1	3.75	95	4.313	110
ESL375.4375	1	3.75	95	4.375	111

COUPLING SPACERS | Inside Diameter Coupling Spacers

- Connect Main and Tender (or Helper) Springs
- Inside Diameter Coupling Spacers for our Most Popular ERS Doublespring Applications
- Lightweight and Durable Anodized Aluminum Design
- CNC Precision Machined for Accuracy



Part Number	Quantity	Spring Diameter Range	
		inch	mm
Coupling Spacer (ID locating main to helper/tender)			
SPACER188	1	1.88	48
SPACER225	1	2.25	57
SPACER250	1	2.50	64
SPACER300	1	3.00	76
SPACER375	1	3.75	95
1-60-00	1		60
1-70-00	1		70

SPRING PERCH ADAPTER | 60mm to 2.50 inch

- Extend Your Range of Available Spring Rates
- Adapts 60mm to 2.50 inch ID SAE Springs
- Lightweight and Durable Anodized Aluminum Design
- CNC Precision Machined for Accuracy



Part Number	Quantity	Spring Diameter Range	
		inch	mm
Adapter			
ADAPTER60-250 (Perch Adapter 60mm to 2.50")	1	60 / 2.50	60 / 64

TORSION RELEASE BEARING - TRB | Smoother Deflection

- Reduce Torsional Binding by Removing Friction During Deflection
- Smoother and More Consistent Spring Action Throughout the Entire Range of Deflection
- Allows For Easier And More Precise Ride Height Adjustment by Eliminating Spring Seat Friction



Part Number	Quantity	Spring Diameter Range	
		inch	mm
Torsion Release Bearing			
TRB188	1	1.88	48
TRB200	1	2.00	51
TRB225	1	2.25	57
TRB250	1	2.50	64
TRB300	1	3.00	76

EIBACH ACCESSORIES

DIFFERENTIAL LOCKER SPRINGS | Tunable Traction

- Extreme-Performance Locker Springs
- Designed for Demanding Racing Applications
- Extensively Tested to Provide Extended Durability
- Improved Differential Performance for Faster Lap Times
- Metallurgy Tailored to Withstand High Differential Temperatures
- Precision Engineered and Manufactured by Eibach Springs



Part Number	Quantity	Load	Load Height
		lbs	inch
Differential Locker Springs			
ELS88	2	88 lbs	0.610
ELS78	2	78 lbs	0.610

BUMP STOPS | Secondary Spring Tuning

- Made From a Race-Proven Micro-Cellular Polyurethane Elastomer
- Tremendous Deflection Potential with Near-Zero Lateral Expansion
- Progressive Compression Characteristics
- Extensive Range of Rates and Dimensions for Maximum Tuning Flexibility



Part Number	Quantity	Length		Inside Diameter		Outside Diameter	
		inch	mm	inch	mm	inch	mm
Bump Stop							
EBS770015	1	1.57	40	0.71	18	2.24	57
EBS770034	1	1.81	46	0.79	20	2.36	60
EBS770014	1	2.10	54	0.71	18	2.24	57
EBS770040	1	2.17	55	0.08	19	2.24	57
EBS770006	1	2.48	63	0.71	18	1.97	50
EBS770021	1	2.48	63	0.81	20	2.05	52
EBS770052	1	2.56	65	0.71	18	1.89	48
EBS770016	1	2.68	68	0.81	20	2.05	52
EBS770020	1	2.68	68	0.79	20	2.36	60
EBS770044	1	2.72	69	0.75	19	2.36	60
EBS770051	1	2.72	69	0.91	23	2.05	52
EBS770045	1	2.76	70	0.71	18	2.36	60
EBS770047	1	2.76	70	0.71	18	2.01	51
EBS770060	1	2.76	70	0.35	9	2.01	51

COILOVER | 1.63" I.D. (Quarter Midget)



Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
3.50 (length in inches)							
New! 0350.163.0080	3.50	89	1.63	41	80	1.43	14
New! 0350.163.0085	3.50	89	1.63	41	85	1.53	15
New! 0350.163.0090	3.50	89	1.63	41	90	1.63	16
New! 0350.163.0095	3.50	89	1.63	41	95	1.73	17
New! 0350.163.0100	3.50	89	1.63	41	100	1.83	18
New! 0350.163.0105	3.50	89	1.63	41	105	1.83	18
New! 0350.163.0110	3.50	89	1.63	41	110	1.94	19
New! 0350.163.0115	3.50	89	1.63	41	115	2.04	20
New! 0350.163.0120	3.50	89	1.63	41	120	2.14	21
New! 0350.163.0125	3.50	89	1.63	41	125	2.24	22
New! 0350.163.0130	3.50	89	1.63	41	130	2.34	23
New! 0350.163.0135	3.50	89	1.63	41	135	2.45	24
New! 0350.163.0140	3.50	89	1.63	41	140	2.55	25
New! 0350.163.0145	3.50	89	1.63	41	145	2.55	25
New! 0350.163.0150	3.50	89	1.63	41	150	2.65	26
5.00 (length in inches)							
New! 0500.163.0070	5.00	127	1.63	41	70	1.22	12
New! 0500.163.0075	5.00	127	1.63	41	75	1.33	13
0500.163.0080	5.00	127	1.63	41	80	1.43	14
0500.163.0085	5.00	127	1.63	41	85	1.53	15
0500.163.0090	5.00	127	1.63	41	90	1.63	16
0500.163.0095	5.00	127	1.63	41	95	1.73	17
0500.163.0100	5.00	127	1.63	41	100	1.83	18
0500.163.0105	5.00	127	1.63	41	105	1.83	18
0500.163.0110	5.00	127	1.63	41	110	1.94	19
0500.163.0115	5.00	127	1.63	41	115	2.04	20
0500.163.0120	5.00	127	1.63	41	120	2.14	21
0500.163.0125	5.00	127	1.63	41	125	2.24	22
0500.163.0130	5.00	127	1.63	41	130	2.34	23
0500.163.0135	5.00	127	1.63	41	135	2.45	24
0500.163.0140	5.00	127	1.63	41	140	2.55	25
0500.163.0145	5.00	127	1.63	41	145	2.55	25
0500.163.0150	5.00	127	1.63	41	150	2.65	26

COILOVER | 1.88" I.D.

8.00 (length in inches)							
0800.188.0100	8.00	203	1.88	48	100	1.83	18
New! 0800.188.0125	8.00	203	1.88	48	125	2.24	22
New! 0800.188.0150	8.00	203	1.88	48	150	2.65	26
New! 0800.188.0175	8.00	203	1.88	48	175	3.16	31
0800.188.0180	8.00	203	1.88	48	180	3.26	32
0800.188.0185	8.00	203	1.88	48	185	3.26	32
0800.188.0200	8.00	203	1.88	48	200	3.57	35
0800.188.0225	8.00	203	1.88	48	225	3.98	39
0800.188.0250	8.00	203	1.88	48	250	4.49	44
0800.188.0280	8.00	203	1.88	48	280	4.99	49
0800.188.0300	8.00	203	1.88	48	300	5.40	53
0800.188.0325	8.00	203	1.88	48	325	5.81	57
0800.188.0350	8.00	203	1.88	48	350	6.22	61

COILOVER | 1.88" I.D.

Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
10.00 (length in inches)							
1000.188.0050	10.00	254	1.88	48	50	0.92	9
1000.188.0060	10.00	254	1.88	48	60	1.12	11
1000.188.0070	10.00	254	1.88	48	70	1.22	12
1000.188.0080	10.00	254	1.88	48	80	1.43	14
1000.188.0090	10.00	254	1.88	48	90	1.63	16
1000.188.0100	10.00	254	1.88	48	100	1.83	18
1000.188.0110	10.00	254	1.88	48	110	1.94	19
1000.188.0120	10.00	254	1.88	48	120	2.14	21
1000.188.0130	10.00	254	1.88	48	130	2.34	23
1000.188.0145	10.00	254	1.88	48	145	2.55	25
1000.188.0160	10.00	254	1.88	48	160	2.85	28
1000.188.0175	10.00	254	1.88	48	175	3.16	31
1000.188.0185	10.00	254	1.88	48	185	3.26	32
1000.188.0200	10.00	254	1.88	48	200	3.57	35
1000.188.0225	10.00	254	1.88	48	225	3.98	39
1000.188.0250	10.00	254	1.88	48	250	4.49	44
1000.188.0275	10.00	254	1.88	48	275	4.89	48
1000.188.0300	10.00	254	1.88	48	300	5.40	53
1000.188.0325	10.00	254	1.88	48	325	5.81	57
1000.188.0350	10.00	254	1.88	48	350	6.22	61
1000.188.0400	10.00	254	1.88	48	400	7.14	70
1000.188.0450	10.00	254	1.88	48	450	8.05	79
Helper (prevents main spring from becoming loose at full droop)							
HELPER188	2.98	76	1.88	48	12	0.22	2
Spacer (ID locating main to helper/tender coupling spacer)							
SPACER188			1.88	48			
Torsion Release Bearing							
TRB188			1.88	48			

SPRING BAGS | 1.88" I.D.

	Quantity	Spring Diameter		Spring Length	
		inch	mm	inch	mm
Protective Spring Bags-Pair (Fits 1.88" I.D. Springs)					
New! ESB12.188	2	1.88	48	10" - 12"	254-305

COILOVER | 2.00" I.D.

4.00 (length in inches)							
0400.200.0350	4.00	102	2.00	51	350	6.22	61
0400.200.0550	4.00	102	2.00	51	550	9.79	96
0400.200.0650	4.00	102	2.00	51	650	11.62	114
0400.200.0700	4.00	102	2.00	51	700	12.54	123
0400.200.0750	4.00	102	2.00	51	750	13.35	131
0400.200.0800	4.00	102	2.00	51	800	14.27	140
0400.200.0950	4.00	102	2.00	51	950	16.92	166
0400.200.1150	4.00	102	2.00	51	1,150	20.49	201
0400.200.1250	4.00	102	2.00	51	1,250	22.32	219
0400.200.1400	4.00	102	2.00	51	1,400	24.97	245
0400.200.1700	4.00	102	2.00	51	1,700	30.38	298
0400.200.1800	4.00	102	2.00	51	1,800	32.11	315
0400.200.1900	4.00	102	2.00	51	1,900	33.94	333

COILOVER | 2.00" I.D.



Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
0400.200.2100	4.00	102	2.00	51	2,100	37.51	368
0400.200.2200	4.00	102	2.00	51	2,200	39.25	385
0400.200.2400	4.00	102	2.00	51	2,400	42.81	420
0400.200.2600	4.00	102	2.00	51	2,600	46.38	455
0400.200.2800	4.00	102	2.00	51	2,800	49.95	490
0400.200.3000	4.00	102	2.00	51	3,000	53.52	525
0400.200.3500	4.00	102	2.00	51	3,500	62.49	613
5.00 (length in inches)							
0500.200.0250	5.00	127	2.00	51	250	4.49	44
0500.200.0400	5.00	127	2.00	51	400	7.14	70
0500.200.0425	5.00	127	2.00	51	425	7.54	74
0500.200.0500	5.00	127	2.00	51	500	8.97	88
0500.200.0550	5.00	127	2.00	51	550	9.79	96
0500.200.0650	5.00	127	2.00	51	650	11.62	114
0500.200.0700	5.00	127	2.00	51	700	12.54	123
0500.200.0725	5.00	127	2.00	51	725	12.95	127
0500.200.0750	5.00	127	2.00	51	750	13.35	131
0500.200.0800	5.00	127	2.00	51	800	14.27	140
0500.200.0950	5.00	127	2.00	51	950	16.92	166
0500.200.1000	5.00	127	2.00	51	1,000	17.84	175
0500.200.1050	5.00	127	2.00	51	1,050	18.76	184
0500.200.1200	5.00	127	2.00	51	1,200	21.41	210
0500.200.1300	5.00	127	2.00	51	1,300	23.17	227
0500.200.1350	5.00	127	2.00	51	1,350	24.06	236
0500.200.1400	5.00	127	2.00	51	1,400	24.97	245
0500.200.1500	5.00	127	2.00	51	1,500	26.81	263
0500.200.1600	5.00	127	2.00	51	1,600	28.54	280
0500.200.1700	5.00	127	2.00	51	1,700	30.38	298
0500.200.1750	5.00	127	2.00	51	1,750	31.19	306
0500.200.2400	5.00	127	2.00	51	2,400	42.81	420
Torsion Release Bearing							
TRB200			2.00	51			

COILOVER | 2.25" I.D.

4.00 (length in inches)							
0400.225.0450	4.00	102	2.25	57	450	8.07	79
0400.225.0500	4.00	102	2.25	57	500	8.97	88
0400.225.0550	4.00	102	2.25	57	550	9.79	96
0400.225.0800	4.00	102	2.25	57	800	14.27	140
0400.225.0825	4.00	102	2.25	57	825	14.68	144
0400.225.0850	4.00	102	2.25	57	850	15.19	149
New! 0400.225.0950	4.00	102	2.25	57	950	16.92	166
0400.225.1000	4.00	102	2.25	57	1,000	17.84	175
0400.225.1075	4.00	102	2.25	57	1,075	19.23	189
0400.225.1100	4.00	102	2.25	57	1,100	19.67	193
0400.225.1200	4.00	102	2.25	57	1,200	21.41	210
0400.225.1250	4.00	102	2.25	57	1,250	22.32	219
0400.225.1300	4.00	102	2.25	57	1,300	23.24	228
0400.225.1350	4.00	102	2.25	57	1,350	24.06	236
0400.225.1400	4.00	102	2.25	57	1,400	24.97	245

Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
0400.225.1800	4.00	102	2.25	57	1,800	32.11	315
0400.225.1900	4.00	102	2.25	57	1,900	33.94	333
0400.225.2000	4.00	102	2.25	57	2,000	35.68	350
0400.225.2300	4.00	102	2.25	57	2,300	41.08	403
0400.225.2400	4.00	102	2.25	57	2,400	42.81	420
0400.225.2500	4.00	102	2.25	57	2,500	44.65	438
0400.225.2600	4.00	102	2.25	57	2,600	46.38	455
0400.225.2800	4.00	102	2.25	57	2,800	49.95	490
0400.225.3000	4.00	102	2.25	57	3,000	53.52	525
0400.225.3200	4.00	102	2.25	57	3,200	57.08	560
0400.225.3400	4.00	102	2.25	57	3,400	60.65	595
5.00 (length in inches)							
0500.225.0350	5.00	127	2.25	57	350	6.22	61
0500.225.0425	5.00	127	2.25	57	425	7.54	74
0500.225.0450	5.00	127	2.25	57	450	8.05	79
0500.225.0500	5.00	127	2.25	57	500	8.97	88
0500.225.0525	5.00	127	2.25	57	525	9.38	92
0500.225.0550	5.00	127	2.25	57	550	9.79	96
0500.225.0600	5.00	127	2.25	57	600	10.70	105
0500.225.0625	5.00	127	2.25	57	625	11.11	109
0500.225.0650	5.00	127	2.25	57	650	11.62	114
0500.225.0675	5.00	127	2.25	57	675	12.03	118
0500.225.0700	5.00	127	2.25	57	700	12.54	123
0500.225.0750	5.00	127	2.25	57	750	13.35	131
0500.225.0800	5.00	127	2.25	57	800	14.27	140
0500.225.0850	5.00	127	2.25	57	850	15.19	149
0500.225.0875	5.00	127	2.25	57	875	15.60	153
0500.225.0900	5.00	127	2.25	57	900	16.11	158
0500.225.0925	5.00	127	2.25	57	925	16.51	162
0500.225.0950	5.00	127	2.25	57	950	16.95	166
0500.225.1000	5.00	127	2.25	57	1,000	17.84	175
0500.225.1050	5.00	127	2.25	57	1,050	18.76	184
0500.225.1100	5.00	127	2.25	57	1,100	19.67	193
0500.225.1150	5.00	127	2.25	57	1,150	20.49	201
0500.225.1200	5.00	127	2.25	57	1,200	21.41	210
0500.225.1250	5.00	127	2.25	57	1,250	22.32	219
0500.225.1300	5.00	127	2.25	57	1,300	23.24	228
0500.225.1350	5.00	127	2.25	57	1,350	24.06	236
0500.225.1400	5.00	127	2.25	57	1,400	24.97	245
0500.225.1450	5.00	127	2.25	57	1,450	25.89	254
0500.225.1500	5.00	127	2.25	57	1,500	26.81	263
0500.225.1525	5.00	127	2.25	57	1,525	27.22	267
0500.225.1550	5.00	127	2.25	57	1,550	27.62	271
0500.225.1600	5.00	127	2.25	57	1,600	28.54	280
0500.225.1700	5.00	127	2.25	57	1,700	30.38	298
0500.225.1750	5.00	127	2.25	57	1,750	31.19	306
0500.225.1800	5.00	127	2.25	57	1,800	32.13	315
0500.225.1850	5.00	127	2.25	57	1,850	33.03	324
0500.225.2100	5.00	127	2.25	57	2,100	37.51	368
0500.225.2400	5.00	127	2.25	57	2,400	42.81	420
0500.225.3100	5.00	127	2.25	57	3,100	55.35	543
0500.225.3400	5.00	127	2.25	57	3,400	60.65	595

COILOVER | 2.25" I.D.



Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
0500.225.3500	5.00	127	2.25	57	3,500	62.49	613
0500.225.3600	5.00	127	2.25	57	3,600	64.22	630
0500.225.4100	5.00	127	2.25	57	4,100	73.19	718
6.00 (length in inches)							
0600.225.0125	6.00	152	2.25	57	125	2.24	22
0600.225.0150	6.00	152	2.25	57	150	2.65	26
0600.225.0175	6.00	152	2.25	57	175	3.16	31
0600.225.0200	6.00	152	2.25	57	200	3.57	35
0600.225.0225	6.00	152	2.25	57	225	3.98	39
0600.225.0250	6.00	152	2.25	57	250	4.49	44
0600.225.0275	6.00	152	2.25	57	275	4.89	48
0600.225.0300	6.00	152	2.25	57	300	5.40	53
0600.225.0325	6.00	152	2.25	57	325	5.81	57
0600.225.0350	6.00	152	2.25	57	350	6.22	61
0600.225.0375	6.00	152	2.25	57	375	6.73	66
0600.225.0400	6.00	152	2.25	57	400	7.14	70
0600.225.0450	6.00	152	2.25	57	450	8.05	79
0600.225.0475	6.00	152	2.25	57	475	8.46	83
0600.225.0500	6.00	152	2.25	57	500	8.97	88
0600.225.0525	6.00	152	2.25	57	525	9.38	92
0600.225.0550	6.00	152	2.25	57	550	9.79	96
0600.225.0575	6.00	152	2.25	57	575	10.30	101
0600.225.0600	6.00	152	2.25	57	600	10.70	105
0600.225.0625	6.00	152	2.25	57	625	11.11	109
0600.225.0650	6.00	152	2.25	57	650	11.62	114
0600.225.0700	6.00	152	2.25	57	700	12.54	123
0600.225.0750	6.00	152	2.25	57	750	13.35	131
0600.225.0800	6.00	152	2.25	57	800	14.27	140
0600.225.0850	6.00	152	2.25	57	850	15.19	149
0600.225.0900	6.00	152	2.25	57	900	16.11	158
0600.225.0950	6.00	152	2.25	57	950	16.92	166
0600.225.1000	6.00	152	2.25	57	1,000	17.84	175
0600.225.1100	6.00	152	2.25	57	1,100	19.67	193
0600.225.1200	6.00	152	2.25	57	1,200	21.41	210
0600.225.1300	6.00	152	2.25	57	1,300	23.24	228
0600.225.1400	6.00	152	2.25	57	1,400	24.97	245
0600.225.1450	6.00	152	2.25	57	1,450	25.89	254
0600.225.1500	6.00	152	2.25	57	1,500	26.81	263
0600.225.1600	6.00	152	2.25	57	1,600	28.54	280
0600.225.1800	6.00	152	2.25	57	1,800	32.11	315
0600.225.2000	6.00	152	2.25	57	2,000	35.68	350
0600.225.2200	6.00	152	2.25	57	2,200	39.25	385
7.00 (length in inches)							
0700.225.0200	7.00	178	2.25	57	200	3.53	35
0700.225.0225	7.00	178	2.25	57	225	3.98	39
0700.225.0250	7.00	178	2.25	57	250	4.49	44
0700.225.0300	7.00	178	2.25	57	300	5.40	53
0700.225.0325	7.00	178	2.25	57	325	5.81	57
0700.225.0350	7.00	178	2.25	57	350	6.22	61
0700.225.0375	7.00	178	2.25	57	375	6.73	66
0700.225.0400	7.00	178	2.25	57	400	7.14	70
0700.225.0425	7.00	178	2.25	57	425	7.54	74

Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
0700.225.0450	7.00	178	2.25	57	450	8.05	79
0700.225.0475	7.00	178	2.25	57	475	8.46	83
0700.225.0500	7.00	178	2.25	57	500	8.97	88
0700.225.0525	7.00	178	2.25	57	525	9.38	92
0700.225.0550	7.00	178	2.25	57	550	9.79	96
0700.225.0600	7.00	178	2.25	57	600	10.70	105
0700.225.0650	7.00	178	2.25	57	650	11.62	114
0700.225.0700	7.00	178	2.25	57	700	12.54	123
0700.225.0750	7.00	178	2.25	57	750	13.35	131
0700.225.0800	7.00	178	2.25	57	800	14.27	140
0700.225.0850	7.00	178	2.25	57	850	15.19	149
0700.225.0900	7.00	178	2.25	57	900	16.11	158
0700.225.1000	7.00	178	2.25	57	1,000	17.84	175
0700.225.1100	7.00	178	2.25	57	1,100	19.67	193
8.00 (length in inches)							
0800.225.0150	8.00	203	2.25	57	150	2.65	26
0800.225.0200	8.00	203	2.25	57	200	3.57	35
0800.225.0225	8.00	203	2.25	57	225	3.98	39
0800.225.0250	8.00	203	2.25	57	250	4.49	44
0800.225.0275	8.00	203	2.25	57	275	4.89	48
0800.225.0300	8.00	203	2.25	57	300	5.40	53
0800.225.0325	8.00	203	2.25	57	325	5.81	57
0800.225.0350	8.00	203	2.25	57	350	6.22	61
0800.225.0375	8.00	203	2.25	57	375	6.73	66
0800.225.0400	8.00	203	2.25	57	400	7.14	70
0800.225.0425	8.00	203	2.25	57	425	7.54	74
0800.225.0450	8.00	203	2.25	57	450	8.05	79
0800.225.0475	8.00	203	2.25	57	475	8.46	83
0800.225.0500	8.00	203	2.25	57	500	8.97	88
0800.225.0525	8.00	203	2.25	57	525	9.38	92
0800.225.0550	8.00	203	2.25	57	550	9.79	96
0800.225.0600	8.00	203	2.25	57	600	10.70	105
0800.225.0650	8.00	203	2.25	57	650	11.62	114
0800.225.0700	8.00	203	2.25	57	700	12.54	123
0800.225.0750	8.00	203	2.25	57	750	13.35	131
0800.225.0800	8.00	203	2.25	57	800	14.27	140
0800.225.0850	8.00	203	2.25	57	850	15.19	149
0800.225.0900	8.00	203	2.25	57	900	16.11	158
0800.225.1000	8.00	203	2.25	57	1,000	17.84	175
9.00 (length in inches)							
0900.225.0175	9.00	229	2.25	57	175	3.14	31
0900.225.0250	9.00	229	2.25	57	250	4.49	44
0900.225.0300	9.00	229	2.25	57	300	5.40	53
0900.225.0350	9.00	229	2.25	57	350	6.22	61
0900.225.0400	9.00	229	2.25	57	400	7.14	70
0900.225.0450	9.00	229	2.25	57	450	8.05	79
0900.225.0500	9.00	229	2.25	57	500	8.97	88
0900.225.0550	9.00	229	2.25	57	550	9.79	96
0900.225.0600	9.00	229	2.25	57	600	10.70	105
0900.225.0700	9.00	229	2.25	57	700	12.54	123
0900.225.0800	9.00	229	2.25	57	800	14.27	140
0900.225.0900	9.00	229	2.25	57	900	16.11	158

COILOVER | 2.25" I.D.



Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
Tender/Linear							
0175.225.0150	2.71	69	2.25	57	150	2.65	26
0175.225.0250	3.35	85	2.25	57	250	4.49	44
0175.225.0300	4.26	108	2.25	57	300	5.40	53
0225.225.0150	3.84	98	2.25	57	150	2.65	26
0225.225.0200	3.76	96	2.25	57	200	3.57	35
New! 0225.225.0250	3.78	96	2.25	57	250	4.49	44
Helper							
HELPER225	3.05	78	2.25	57	12	0.21	2
Spacer (ID locating main to helper/tender coupling spacer)							
SPACER225			2.25	57			
Torsion Release Bearing							
TRB225			2.25	57			

SPRING BAGS | 2.25" I.D.

Protective Spring Bags-Pair (Fits 2.25" I.D. Springs)	Quantity	Spring Diameter		Spring Length	
		inch	mm	inch	mm
New! ESB12.225	2	2.25	57	10" - 12"	254-305

ELITE SERIES | 2.50" I.D.

4.00 (length in inches)							
New! ES0400.250.0400	4.00	102	2.50	64	400	7.14	70
New! ES0400.250.0500	4.00	102	2.50	64	500	8.93	88
New! ES0400.250.0600	4.00	102	2.50	64	600	10.71	105
6.00 (length in inches)							
New! ES0600.250.0300	6.00	152	2.50	64	300	5.36	53
New! ES0600.250.0350	6.00	152	2.50	64	350	6.25	61
New! ES0600.250.0400	6.00	152	2.50	64	400	7.14	70
New! ES0600.250.0450	6.00	152	2.50	64	450	8.04	79
New! ES0600.250.0500	6.00	152	2.50	64	500	8.93	88
New! ES0600.250.0550	6.00	152	2.50	64	550	9.82	96
New! ES0600.250.0600	6.00	152	2.50	64	600	10.71	105
New! ES0600.250.0650	6.00	152	2.50	64	650	11.61	114
New! ES0600.250.0700	6.00	152	2.50	64	700	12.50	123
New! ES0600.250.0750	6.00	152	2.50	64	750	13.39	131
New! ES0600.250.0800	6.00	152	2.50	64	800	14.29	140
New! ES0600.250.0850	6.00	152	2.50	64	850	15.18	149
New! ES0600.250.0900	6.00	152	2.50	64	900	16.07	158
8.00 (length in inches)							
New! ES0800.250.0300	8.00	203	2.50	64	300	5.36	53
New! ES0800.250.0350	8.00	203	2.50	64	350	6.25	61
New! ES0800.250.0400	8.00	203	2.50	64	400	7.14	70
New! ES0800.250.0450	8.00	203	2.50	64	500	8.93	88
New! ES0800.250.0550	8.00	203	2.50	64	550	9.82	96
New! ES0800.250.0600	8.00	203	2.50	64	600	10.71	105
New! ES0800.250.0650	8.00	203	2.50	64	650	11.61	114
New! ES0800.250.0700	8.00	203	2.50	64	700	12.50	123
Tender/Progressive							
0175.250.1300	3.55	90	2.50	64	600 / 1300	10.7 / 23.2	105 / 228
0200.250.0550	3.50	89	2.50	64	250 / 550	4.5 / 9.8	44 / 96

ELITE SERIES | 2.50" I.D.

Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
Helper							
HELPER250	3.03	77	2.50	64	11	0.19	2
Spacer (ID locating main to helper/tender coupling spacer)							
SPACER250			2.50	64			
Isolator (Delrin Seat Plate)							
ISOLATOR250			2.50	64			
Torsion Release Bearing							
TRB250			2.50	64			

XT BARREL | 2.50" I.D. Extreme Travel

10.00 (length in inches) XT Barrel (Extreme Travel)								
New!	1000.2530.0225	10.00	254	2.50 / 3.00	64 / 76	225	3.98	39
New!	1000.2530.0250	10.00	254	2.50 / 3.00	64 / 76	250	4.49	44
New!	1000.2530.0275	10.00	254	2.50 / 3.00	64 / 76	275	4.89	48
	1000.2530.0300	10.00	254	2.50 / 3.00	64 / 76	300	5.40	53
	1000.2530.0325	10.00	254	2.50 / 3.00	64 / 76	325	5.81	57
	1000.2530.0350	10.00	254	2.50 / 3.00	64 / 76	350	6.22	61
	1000.2530.0375	10.00	254	2.50 / 3.00	64 / 76	375	6.73	66
	1000.2530.0400	10.00	254	2.50 / 3.00	64 / 76	400	7.14	70
	1000.2530.0425	10.00	254	2.50 / 3.00	64 / 76	425	7.54	74
	1000.2530.0450	10.00	254	2.50 / 3.00	64 / 76	450	8.05	79
	1000.2530.0475	10.00	254	2.50 / 3.00	64 / 76	475	8.46	83
	1000.2530.0500	10.00	254	2.50 / 3.00	64 / 76	500	8.97	88
	1000.2530.0525	10.00	254	2.50 / 3.00	64 / 76	525	9.38	92
	1000.2530.0550	10.00	254	2.50 / 3.00	64 / 76	550	9.79	96
	1000.2530.0575	10.00	254	2.50 / 3.00	64 / 76	575	10.30	101
12.00 (length in inches) XT Barrel (Extreme Travel)								
	1200.2530.0100	12.00	305	2.50 / 3.00	64 / 76	100	1.83	18
	1200.2530.0125	12.00	305	2.50 / 3.00	64 / 76	125	2.24	22
	1200.2530.0150	12.00	305	2.50 / 3.00	64 / 76	150	2.65	26
	1200.2530.0175	12.00	305	2.50 / 3.00	64 / 76	175	3.16	31
	1200.2530.0200	12.00	305	2.50 / 3.00	64 / 76	200	3.57	35
	1200.2530.0225	12.00	305	2.50 / 3.00	64 / 76	225	3.98	39
	1200.2530.0250	12.00	305	2.50 / 3.00	64 / 76	250	4.49	44
	1200.2530.0275	12.00	305	2.50 / 3.00	64 / 76	275	4.89	48
	1200.2530.0300	12.00	305	2.50 / 3.00	64 / 76	300	5.40	53
	1200.2530.0325	12.00	305	2.50 / 3.00	64 / 76	325	5.81	57
	1200.2530.0350	12.00	305	2.50 / 3.00	64 / 76	350	6.22	61
	1200.2530.0375	12.00	305	2.50 / 3.00	64 / 76	375	6.73	66
	1200.2530.0400	12.00	305	2.50 / 3.00	64 / 76	400	7.14	70
	1200.2530.0425	12.00	305	2.50 / 3.00	64 / 76	425	7.54	74
14.00 (length in inches) XT Barrel (Extreme Travel)								
New!	1400.2530.0100	14.00	356	2.50 / 3.00	64 / 76	100	1.83	18
	1400.2530.0125	14.00	356	2.50 / 3.00	64 / 76	125	2.24	22
	1400.2530.0150	14.00	356	2.50 / 3.00	64 / 76	150	2.65	26
	1400.2530.0175	14.00	356	2.50 / 3.00	64 / 76	175	3.16	31
	1400.2530.0200	14.00	356	2.50 / 3.00	64 / 76	200	3.57	35
	1400.2530.0225	14.00	356	2.50 / 3.00	64 / 76	225	3.98	39
	1400.2530.0250	14.00	356	2.50 / 3.00	64 / 76	250	4.49	44
16.00 (length in inches) XT Barrel (Extreme Travel)								
New!	1600.2530.0125	16.00	406	2.50 / 3.00	64 / 76	125	2.24	22

XT BARREL | 2.50" I.D. Extreme Travel



Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
New! 1600.2530.0150	16.00	406	2.50 / 3.00	64 / 76	150	2.65	26
New! 1600.2530.0175	16.00	406	2.50 / 3.00	64 / 76	175	3.16	31
Torsion Release Bearing							
TRB250			2.50	64			

SPRING BAGS | 2.50" I.D.

Protective Spring Bags-Pair (Fits 2.50" I.D. XT Barrel Springs)	Quantity	Spring Diameter		Spring Length	
		inch	mm	inch	mm
ESB12.300	2	2.50-3.00	64-76	10" - 12"	254-305
ESB14.300	2	2.50-3.00	64-76	12" - 14"	305-356
ESB16.300	2	2.50-3.00	64-76	14" - 16"	356-406

COILOVER | 2.50" I.D.

6.00 (length in inches)							
0600.250.0400	6.00	152	2.50	64	400	7.14	70
0600.250.0450	6.00	152	2.50	64	450	8.05	79
0600.250.0500	6.00	152	2.50	64	500	8.97	88
0600.250.0550	6.00	152	2.50	64	550	9.79	96
0600.250.0600	6.00	152	2.50	64	600	10.70	105
0600.250.0650	6.00	152	2.50	64	650	11.62	114
0600.250.0700	6.00	152	2.50	64	700	12.54	123
0600.250.0750	6.00	152	2.50	64	750	13.35	131
0600.250.0800	6.00	152	2.50	64	800	14.27	140
0600.250.0850	6.00	152	2.50	64	850	15.19	149
0600.250.0900	6.00	152	2.50	64	900	16.11	158
0600.250.0950	6.00	152	2.50	64	950	16.92	166
0600.250.0975	6.00	152	2.50	64	975	17.43	171
0600.250.1000	6.00	152	2.50	64	1,000	17.84	175
0600.250.1100	6.00	152	2.50	64	1,100	19.67	193
0600.250.1150	6.00	152	2.50	64	1,150	20.49	201
0600.250.1200	6.00	152	2.50	64	1,200	21.41	210
0600.250.1300	6.00	152	2.50	64	1,300	23.24	228
0600.250.1450	6.00	152	2.50	64	1,450	25.89	254
7.00 (length in inches)							
0700.250.0275	7.00	178	2.50	64	275	4.89	48
0700.250.0300	7.00	178	2.50	64	300	5.40	53
0700.250.0325	7.00	178	2.50	64	325	5.81	57
0700.250.0350	7.00	178	2.50	64	350	6.22	61
0700.250.0375	7.00	178	2.50	64	375	6.73	66
0700.250.0400	7.00	178	2.50	64	400	7.14	70
0700.250.0450	7.00	178	2.50	64	450	8.05	79
0700.250.0500	7.00	178	2.50	64	500	8.97	88
0700.250.0550	7.00	178	2.50	64	550	9.79	96
0700.250.0600	7.00	178	2.50	64	600	10.70	105
0700.250.0650	7.00	178	2.50	64	650	11.62	114
0700.250.0700	7.00	178	2.50	64	700	12.54	123
New! 0700.250.0750	7.00	178	2.50	64	750	13.35	131
0700.250.0800	7.00	178	2.50	64	800	14.27	140
0700.250.0900	7.00	178	2.50	64	900	16.11	158
0700.250.1000	7.00	178	2.50	64	1,000	17.84	175
0700.250.1100	7.00	178	2.50	64	1,100	19.67	193

COILOVER | 2.50" I.D.

Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
8.00 (length in inches)							
0800.250.0150	8.00	203	2.50	64	150	2.65	26
0800.250.0175	8.00	203	2.50	64	175	3.16	31
0800.250.0200	8.00	203	2.50	64	200	3.57	35
0800.250.0225	8.00	203	2.50	64	225	3.98	39
0800.250.0250	8.00	203	2.50	64	250	4.49	44
0800.250.0275	8.00	203	2.50	64	275	4.89	48
0800.250.0300	8.00	203	2.50	64	300	5.40	53
0800.250.0325	8.00	203	2.50	64	325	5.81	57
0800.250.0350	8.00	203	2.50	64	350	6.22	61
0800.250.0375	8.00	203	2.50	64	375	6.73	66
0800.250.0400	8.00	203	2.50	64	400	7.14	70
0800.250.0425	8.00	203	2.50	64	425	7.54	74
0800.250.0450	8.00	203	2.50	64	450	8.05	79
0800.250.0475	8.00	203	2.50	64	475	8.46	83
0800.250.0500	8.00	203	2.50	64	500	8.97	88
0800.250.0525	8.00	203	2.50	64	525	9.38	92
0800.250.0550	8.00	203	2.50	64	550	9.79	96
0800.250.0600	8.00	203	2.50	64	600	10.70	105
0800.250.0650	8.00	203	2.50	64	650	11.62	114
0800.250.0700	8.00	203	2.50	64	700	12.54	123
0800.250.0750	8.00	203	2.50	64	750	13.35	131
0800.250.0800	8.00	203	2.50	64	800	14.27	140
0800.250.0825	8.00	203	2.50	64	825	14.68	144
0800.250.0850	8.00	203	2.50	64	850	15.19	149
0800.250.0900	8.00	203	2.50	64	900	16.11	158
0800.250.0950	8.00	203	2.50	64	950	16.92	166
0800.250.1000	8.00	203	2.50	64	1,000	17.84	175
0800.250.1025	8.00	203	2.50	64	1,025	18.25	179
0800.250.1100	8.00	203	2.50	64	1,100	19.67	193
0800.250.1200	8.00	203	2.50	64	1,200	21.41	210
8.00 (length in inches) (Silver)							
0800.250.0150S	8.00	203	2.50	64	150	2.65	26
0800.250.0200S	8.00	203	2.50	64	200	3.57	35
0800.250.0250S	8.00	203	2.50	64	250	4.49	44
0800.250.0300S	8.00	203	2.50	64	300	5.40	53
0800.250.0350S	8.00	203	2.50	64	350	6.22	61
0800.250.0400S	8.00	203	2.50	64	400	7.14	70
0800.250.0500S	8.00	203	2.50	64	500	8.97	88
0800.250.0550S	8.00	203	2.50	64	550	9.79	96
0800.250.0600S	8.00	203	2.50	64	600	10.70	105
10.00 (length in inches)							
1000.250.0100	10.00	254	2.50	64	100	1.83	18
1000.250.0150	10.00	254	2.50	64	150	2.65	26
1000.250.0162	10.00	254	2.50	64	162	2.85	28
1000.250.0175	10.00	254	2.50	64	175	3.16	31
1000.250.0200	10.00	254	2.50	64	200	3.57	35
1000.250.0225	10.00	254	2.50	64	225	3.98	39
1000.250.0250	10.00	254	2.50	64	250	4.49	44
1000.250.0275	10.00	254	2.50	64	275	4.89	48
1000.250.0300	10.00	254	2.50	64	300	5.40	53
1000.250.0325	10.00	254	2.50	64	325	5.81	57

Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
1000.250.0350	10.00	254	2.50	64	350	6.22	61
1000.250.0375	10.00	254	2.50	64	375	6.73	66
1000.250.0400	10.00	254	2.50	64	400	7.14	70
1000.250.0425	10.00	254	2.50	64	425	7.54	74
1000.250.0450	10.00	254	2.50	64	450	8.05	79
New! 1000.250.0475	10.00	254	2.50	64	475	8.46	83
1000.250.0500	10.00	254	2.50	64	500	8.97	88
1000.250.0525	10.00	254	2.50	64	525	9.38	92
1000.250.0550	10.00	254	2.50	64	550	9.79	96
1000.250.0575	10.00	254	2.50	64	575	10.30	101
1000.250.0600	10.00	254	2.50	64	600	10.70	105
1000.250.0650	10.00	254	2.50	64	650	11.62	114
1000.250.0700	10.00	254	2.50	64	700	12.54	123
1000.250.0750	10.00	254	2.50	64	750	13.35	131
1000.250.0800	10.00	254	2.50	64	800	14.27	140
10.00 (length in inches) (Silver)							
1000.250.0100S	10.00	254	2.50	64	100	1.83	18
1000.250.0150S	10.00	254	2.50	64	150	2.65	26
1000.250.0175S	10.00	254	2.50	64	175	3.16	31
1000.250.0200S	10.00	254	2.50	64	200	3.57	35
1000.250.0225S	10.00	254	2.50	64	225	3.98	39
1000.250.0250S	10.00	254	2.50	64	250	4.49	44
1000.250.0275S	10.00	254	2.50	64	275	4.89	48
1000.250.0300S	10.00	254	2.50	64	300	5.40	53
1000.250.0325S	10.00	254	2.50	64	325	5.81	57
1000.250.0350S	10.00	254	2.50	64	350	6.22	61
1000.250.0375S	10.00	254	2.50	64	375	6.73	66
1000.250.0400S	10.00	254	2.50	64	400	7.14	70
1000.250.0425S	10.00	254	2.50	64	425	7.54	74
1000.250.0450S	10.00	254	2.50	64	450	8.05	79
1000.250.0500S	10.00	254	2.50	64	500	8.97	88
1000.250.0550S	10.00	254	2.50	64	550	9.79	96
1000.250.0600S	10.00	254	2.50	64	600	10.70	105
1000.250.0650S	10.00	254	2.50	64	650	11.62	114
1000.250.0700S	10.00	254	2.50	64	700	12.54	123
1000.250.0750S	10.00	254	2.50	64	750	13.35	131
1000.250.0800S	10.00	254	2.50	64	800	14.27	140
12.00 (length in inches)							
New! 1200.250.0080	12.00	305	2.50	64	80	1.43	14
1200.250.0090	12.00	305	2.50	64	90	1.63	16
1200.250.0100	12.00	305	2.50	64	100	1.83	18
1200.250.0110	12.00	305	2.50	64	110	1.94	19
1200.250.0120	12.00	305	2.50	64	120	2.14	21
1200.250.0125	12.00	305	2.50	64	125	2.24	22
1200.250.0130	12.00	305	2.50	64	130	2.34	23
1200.250.0140	12.00	305	2.50	64	140	2.55	25
1200.250.0150	12.00	305	2.50	64	150	2.65	26
1200.250.0165	12.00	305	2.50	64	165	2.96	29
1200.250.0175	12.00	305	2.50	64	175	3.16	31
1200.250.0185	12.00	305	2.50	64	185	3.26	32
1200.250.0200	12.00	305	2.50	64	200	3.57	35
1200.250.0225	12.00	305	2.50	64	225	3.98	39

Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
1200.250.0250	12.00	305	2.50	64	250	4.49	44
1200.250.0275	12.00	305	2.50	64	275	4.89	48
1200.250.0300	12.00	305	2.50	64	300	5.40	53
1200.250.0325	12.00	305	2.50	64	325	5.81	57
1200.250.0350	12.00	305	2.50	64	350	6.22	61
1200.250.0375	12.00	305	2.50	64	375	6.73	66
1200.250.0400	12.00	305	2.50	64	400	7.14	70
1200.250.0425	12.00	305	2.50	64	425	7.54	74
1200.250.0450	12.00	305	2.50	64	450	8.05	79
1200.250.0475	12.00	305	2.50	64	475	8.46	83
1200.250.0525	12.00	305	2.50	64	525	9.38	92
1200.250.0600	12.00	305	2.50	64	600	10.70	105
1200.250.0625	12.00	305	2.50	64	625	11.11	109
1200.250.0800	12.00	305	2.50	64	800	14.27	140
12.00 (length in inches) (Silver)							
1200.250.0100S	12.00	305	2.50	64	100	1.83	18
1200.250.0125S	12.00	305	2.50	64	125	2.24	22
1200.250.0150S	12.00	305	2.50	64	150	2.65	26
1200.250.0175S	12.00	305	2.50	64	175	3.16	31
1200.250.0200S	12.00	305	2.50	64	200	3.57	35
1200.250.0225S	12.00	305	2.50	64	225	3.98	39
1200.250.0250S	12.00	305	2.50	64	250	4.49	44
1200.250.0275S	12.00	305	2.50	64	275	4.89	48
1200.250.0300S	12.00	305	2.50	64	300	5.40	53
1200.250.0325S	12.00	305	2.50	64	325	5.81	57
1200.250.0350S	12.00	305	2.50	64	350	6.22	61
1200.250.0375S	12.00	305	2.50	64	375	6.73	66
1200.250.0400S	12.00	305	2.50	64	400	7.14	70
1200.250.0425S	12.00	305	2.50	64	425	7.54	74
1200.250.0450S	12.00	305	2.50	64	450	8.05	79
1200.250.0475S	12.00	305	2.50	64	475	8.46	83
1200.250.0500S	12.00	305	2.50	64	500	8.97	88
1200.250.0525S	12.00	305	2.50	64	525	9.38	92
1200.250.0550S	12.00	305	2.50	64	550	9.79	96
1200.250.0600S	12.00	305	2.50	64	600	10.70	105
1200.250.0650S	12.00	305	2.50	64	650	11.62	114
1200.250.0700S	12.00	305	2.50	64	700	12.54	123
1200.250.0750S	12.00	305	2.50	64	750	13.35	131
1200.250.0800S	12.00	305	2.50	64	800	14.27	140
1200.250.0900S	12.00	305	2.50	64	900	16.11	158
14.00 (length in inches)							
1400.250.0080	14.00	356	2.50	64	80	1.43	14
1400.250.0090	14.00	356	2.50	64	90	1.63	16
1400.250.0095	14.00	356	2.50	64	95	1.73	17
1400.250.0100	14.00	356	2.50	64	100	1.83	18
1400.250.0110	14.00	356	2.50	64	110	1.94	19
1400.250.0120	14.00	356	2.50	64	120	2.14	21
1400.250.0130	14.00	356	2.50	64	130	2.34	23
1400.250.0140	14.00	356	2.50	64	140	2.55	25
1400.250.0150	14.00	356	2.50	64	150	2.65	26
1400.250.0165	14.00	356	2.50	64	165	2.96	29
1400.250.0175	14.00	356	2.50	64	175	3.16	31

Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
1400.250.0185	14.00	356	2.50	64	185	3.26	32
1400.250.0200	14.00	356	2.50	64	200	3.57	35
1400.250.0225	14.00	356	2.50	64	225	3.98	39
1400.250.0250	14.00	356	2.50	64	250	4.49	44
1400.250.0275	14.00	356	2.50	64	275	4.89	48
1400.250.0300	14.00	356	2.50	64	300	5.40	53
1400.250.0325	14.00	356	2.50	64	325	5.81	57
1400.250.0350	14.00	356	2.50	64	350	6.22	61
1400.250.0400	14.00	356	2.50	64	400	7.14	70
1400.250.0450	14.00	356	2.50	64	450	8.05	79
1400.250.0500	14.00	356	2.50	64	500	8.97	88
14.00 (length in inches) (Silver)							
1400.250.0100S	14.00	356	2.50	64	100	1.83	18
1400.250.0125S	14.00	356	2.50	64	125	2.24	22
1400.250.0150S	14.00	356	2.50	64	150	2.65	26
1400.250.0175S	14.00	356	2.50	64	175	3.16	31
1400.250.0185S	14.00	356	2.50	64	185	3.26	32
1400.250.0200S	14.00	356	2.50	64	200	3.57	35
1400.250.0225S	14.00	356	2.50	64	225	3.98	39
1400.250.0250S	14.00	356	2.50	64	250	4.49	44
1400.250.0275S	14.00	356	2.50	64	275	4.89	48
1400.250.0300S	14.00	356	2.50	64	300	5.40	53
1400.250.0350S	14.00	356	2.50	64	350	6.22	61
1400.250.0400S	14.00	356	2.50	64	400	7.14	70
1400.250.0450S	14.00	356	2.50	64	450	8.05	79
1400.250.0500S	14.00	356	2.50	64	500	8.97	88
1400.250.0550S	14.00	356	2.50	64	550	9.79	96
1400.250.0600S	14.00	356	2.50	64	600	10.70	105
1400.250.0650S	14.00	356	2.50	64	650	11.62	114
16.00 (length in inches) (Silver)							
1600.250.0200S	16.00	406	2.50	64	200	3.57	35
1600.250.0250S	16.00	406	2.50	64	250	4.49	44
1600.250.0300S	16.00	406	2.50	64	300	5.40	53
1600.250.0350S	16.00	406	2.50	64	350	6.22	61
1600.250.0400S	16.00	406	2.50	64	400	7.14	70
1600.250.0450S	16.00	406	2.50	64	450	8.05	79
1600.250.0500S	16.00	406	2.50	64	500	8.97	88
1600.250.0550S	16.00	406	2.50	64	550	9.79	96
1600.250.0600S	16.00	406	2.50	64	600	10.70	105
1600.250.0650S	16.00	406	2.50	64	650	11.62	114
1600.250.0700S	16.00	406	2.50	64	700	12.54	123
1600.250.0750S	16.00	406	2.50	64	750	13.35	131
Tender/Linear							
0175.250.0150	2.64	67	2.50	64	150	2.65	26
0175.250.0200	3.05	77	2.50	64	200	3.57	35
0175.250.0250	2.79	71	2.50	64	250	4.49	44
0175.250.0300	3.27	83	2.50	64	300	5.40	53
0200.250.1300	2.01	51	2.50	64	1,300	23.24	228
0225.250.0150	3.90	99	2.50	64	150	2.65	26
0225.250.0200	3.54	90	2.50	64	200	3.57	35
0225.250.0250	3.94	100	2.50	64	250	4.49	44
0225.250.0300	3.94	100	2.50	64	300	5.40	53

COILOVER | 2.50" I.D.

Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
Tender/Progressive							
0175.250.1300	3.55	90	2.50	64	600 / 1300	10.7 / 23.2	105 / 228
0200.250.0550	3.50	89	2.50	64	250 / 550	4.5 / 9.8	44 / 96
Helper							
HELPER250	3.03	77	2.50	64	11	0.19	2
Spacer (ID locating main to helper/tender coupling spacer)							
SPACER250			2.50	64			
Adapter							
ADAPTER60-250			60 / 2.50	60 / 2.50			
Isolator (Delrin Seat Plate)							
ISOLATOR250			2.50	64			
Torsion Release Bearing							
TRB250			2.50	64			

COIL SLEEVE | 2.50" I.D.

Coil Sleeve (Fits 2.50" I.D. Springs)	Spring Diameter Range		Spring Wire Diameter Range		Coil Sleeve Length	
	inch	mm	inch	mm	inch	mm
CS3001	2.50-3.50	64-89	0.423-0.541	11-14	10.31	262
CS3002	2.50-3.50	64-89	0.551-0.650	14-17	10.31	262

SPRING BAGS | 2.50" I.D.

	Quantity	Spring Diameter		Spring Length	
		inch	mm	inch	mm
Protective Spring Bags-Pair (Fits 2.50" I.D. Springs)					
ESB10.250	2	2.50	64	8" - 10"	203-254
ESB12.250	2	2.50	64	10" - 12"	254-305
ESB14.250	2	2.50	64	12" - 14"	305-356
ESB16.250	2	2.50	64	14" - 16"	356-406
Protective Neoprene Spring Bags-Pair (Fits 2.50" I.D. Springs)					
New! ESN18.250	2	2.50	64	18" - 20"	457-508
New! ESN20.250	2	2.50	64	20" - 22"	508-559
New! ESN22.250	2	2.50	64	22" - 24"	559-610
New! ESN26.250	2	2.50	64	26" - 28"	660-711
New! ESN30.250	2	2.50	64	30" - 32"	762-813

COILOVER | 3.00" I.D.

4.00 (length in inches) (Silver)							
0400.300.0500S	4.00	102	3.00	76	500	8.97	88
6.00 (length in inches) (Silver)							
New! 0600.300.0250S	6.00	152	3.00	76	250	4.49	44
New! 0600.300.0300S	6.00	152	3.00	76	300	5.40	53
New! 0600.300.0350S	6.00	152	3.00	76	350	6.22	61
New! 0600.300.0400S	6.00	152	3.00	76	400	7.14	70
New! 0600.300.0450S	6.00	152	3.00	76	450	8.05	79
8.00 (length in inches) (Silver)							
0800.300.0100S	8.00	203	3.00	76	100	1.83	18
10.00 (length in inches) (Silver)							
1000.300.0100S	10.00	254	3.00	76	100	1.83	18
1000.300.0150S	10.00	254	3.00	76	150	2.65	26
1000.300.0200S	10.00	254	3.00	76	200	3.57	35
1000.300.0250S	10.00	254	3.00	76	250	4.49	44
1000.300.0300S	10.00	254	3.00	76	300	5.40	53

Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
12.00 (length in inches) (Silver)							
1200.300.0100S	12.00	305	3.00	76	100	1.83	18
1200.300.0125S	12.00	305	3.00	76	125	2.24	22
1200.300.0150S	12.00	305	3.00	76	150	2.65	26
1200.300.0175S	12.00	305	3.00	76	175	3.16	31
1200.300.0200S	12.00	305	3.00	76	200	3.57	35
1200.300.0225S	12.00	305	3.00	76	225	3.98	39
1200.300.0250S	12.00	305	3.00	76	250	4.49	44
1200.300.0275S	12.00	305	3.00	76	275	4.89	48
1200.300.0300S	12.00	305	3.00	76	300	5.40	53
1200.300.0325S	12.00	305	3.00	76	325	5.81	57
1200.300.0350S	12.00	305	3.00	76	350	6.22	61
1200.300.0375S	12.00	305	3.00	76	375	6.73	66
1200.300.0400S	12.00	305	3.00	76	400	7.14	70
1200.300.0450S	12.00	305	3.00	76	450	8.05	79
1200.300.0500S	12.00	305	3.00	76	500	8.97	88
1200.300.0600S	12.00	305	3.00	76	600	10.70	105
14.00 (length in inches) (Silver)							
1400.300.0125S	14.00	356	3.00	76	125	2.24	22
1400.300.0150S	14.00	356	3.00	76	150	2.65	26
1400.300.0175S	14.00	356	3.00	76	175	3.16	31
1400.300.0200S	14.00	356	3.00	76	200	3.57	35
1400.300.0225S	14.00	356	3.00	76	225	3.98	39
1400.300.0250S	14.00	356	3.00	76	250	4.49	44
1400.300.0275S	14.00	356	3.00	76	275	4.89	48
1400.300.0300S	14.00	356	3.00	76	300	5.40	53
1400.300.0325S	14.00	356	3.00	76	325	5.81	57
1400.300.0350S	14.00	356	3.00	76	350	6.22	61
1400.300.0400S	14.00	356	3.00	76	400	7.14	70
1400.300.0450S	14.00	356	3.00	76	450	8.05	79
1400.300.0500S	14.00	356	3.00	76	500	8.97	88
1400.300.0550S	14.00	356	3.00	76	550	9.79	96
1400.300.0600S	14.00	356	3.00	76	600	10.70	105
1400.300.0650S	14.00	356	3.00	76	650	11.62	114
New! 1400.300.0700S	14.00	356	3.00	76	700	12.54	123
16.00 (length in inches) (Silver)							
1600.300.0075S	16.00	406	3.00	76	75	1.33	13
1600.300.0100S	16.00	406	3.00	76	100	1.83	18
1600.300.0125S	16.00	406	3.00	76	125	2.24	22
1600.300.0150S	16.00	406	3.00	76	150	2.65	26
1600.300.0175S	16.00	406	3.00	76	175	3.16	31
1600.300.0200S	16.00	406	3.00	76	200	3.57	35
1600.300.0225S	16.00	406	3.00	76	225	3.98	39
1600.300.0250S	16.00	406	3.00	76	250	4.49	44
1600.300.0300S	16.00	406	3.00	76	300	5.40	53
1600.300.0350S	16.00	406	3.00	76	350	6.22	61
1600.300.0400S	16.00	406	3.00	76	400	7.14	70
1600.300.0450S	16.00	406	3.00	76	450	8.05	79
1600.300.0500S	16.00	406	3.00	76	500	8.97	88
1600.300.0550S	16.00	406	3.00	76	550	9.79	96
1600.300.0600S	16.00	406	3.00	76	600	10.70	105
1600.300.0700S	16.00	406	3.00	76	700	12.54	123

COILOVER | 3.00" I.D.

Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
1600.300.0800S	16.00	406	3.00	76	800	14.27	140
18.00 (length in inches) (Silver)							
1800.300.0200S	18.00	457	3.00	76	200	3.57	35
1800.300.0300S	18.00	457	3.00	76	300	5.40	53
1800.300.0400S	18.00	457	3.00	76	400	7.14	70
1800.300.0450S	18.00	457	3.00	76	450	8.05	79
1800.300.0500S	18.00	457	3.00	76	500	8.97	88
1800.300.0550S	18.00	457	3.00	76	550	9.79	96
1800.300.0600S	18.00	457	3.00	76	600	10.70	105
1800.300.0650S	18.00	457	3.00	76	650	11.62	114
1800.300.0700S	18.00	457	3.00	76	700	12.54	123
1800.300.0800S	18.00	457	3.00	76	800	14.27	140
Tender/Linear							
0350.300.0050	4.72	120	3.00	76	50	0.92	9
Helper							
HELPER300	4.85	123	3.00	76	6	0.11	1
Spacer (ID locating main to helper/tender coupling spacer)							
SPACER300			3.00	76			
Torsion Release Bearing							
TRB300			3.00	76			

COIL SLEEVE | 3.00" I.D.

Coil Sleeve (Fits 3.00" I.D. Springs)	Spring Diameter Range		Spring Wire Diameter Range		Coil Sleeve Length	
	inch	mm	inch	mm	inch	mm
CS3001	2.50-3.50	64-89	0.423-0.541	11-14	10.31	262
CS3002	2.50-3.50	64-89	0.551-0.650	14-17	10.31	262

SPRING BAGS | 3.00" I.D.

	Quantity	Spring Diameter		Spring Length	
		inch	mm	inch	mm
Protective Spring Bags-Pair (Fits 3.00" I.D. Springs)					
ESB12.300	2	3.00	76	10" - 12"	254-305
ESB14.300	2	3.00	76	12" - 14"	305-356
ESB16.300	2	3.00	76	14" - 16"	356-406
Protective Neoprene Spring Bags-Pair (Fits 3.00" I.D. Springs)					
New! ESN20.300	2	3.00	76	20" - 22"	508-559
New! ESN22.300	2	3.00	76	22" - 24"	559-610

COILOVER | 3.75" I.D.

8.00 (length in inches) (Silver)							
New! 0800.375.0300S	8.00	203	3.75	95	300	5.40	53
10.00 (length in inches) (Silver)							
1000.375.0250S	10.00	254	3.75	95	250	4.49	44
1000.375.0300S	10.00	254	3.75	95	300	5.40	53
1000.375.0350S	10.00	254	3.75	95	350	6.22	61
1000.375.0400S	10.00	254	3.75	95	400	7.14	70
1000.375.0450S	10.00	254	3.75	95	450	8.05	79
1000.375.0500S	10.00	254	3.75	95	500	8.97	88

Part Number	Length		Inside Diameter		Rate		
	inch	mm	inch	mm	lbs/inch	kg/mm	N/mm
12.00 (length in inches) (Silver)							
1200.375.0200S	12.00	305	3.75	95	200	3.57	35
1200.375.0250S	12.00	305	3.75	95	250	4.49	44
1200.375.0300S	12.00	305	3.75	95	300	5.40	53
1200.375.0350S	12.00	305	3.75	95	350	6.22	61
1200.375.0400S	12.00	305	3.75	95	400	7.14	70
1200.375.0500S	12.00	305	3.75	95	500	8.97	88
1200.375.0700S	12.00	305	3.75	95	700	12.54	123
14.00 (length in inches) (Silver)							
1400.375.0300S	14.00	356	3.75	95	300	5.40	53
1400.375.0350S	14.00	356	3.75	95	350	6.22	61
1400.375.0400S	14.00	356	3.75	95	400	7.14	70
1400.375.0450S	14.00	356	3.75	95	450	8.05	79
18.00 (length in inches) (Silver)							
1800.375.0700S	18.00	457	3.75	95	700	12.54	123
1800.375.0750S	18.00	457	3.75	95	750	13.35	131
1800.375.0800S	18.00	457	3.75	95	800	14.27	140
20.00 (length in inches) (Silver)							
2000.375.0300S	20.00	508	3.75	95	300	5.40	53
2000.375.0400S	20.00	508	3.75	95	400	7.14	70
2000.375.0500S	20.00	508	3.75	95	500	8.97	88
2000.375.0600S	20.00	508	3.75	95	600	10.70	105
2000.375.0650S	20.00	508	3.75	95	650	11.62	114
2000.375.0675S	20.00	508	3.75	95	675	12.03	118
2000.375.0700S	20.00	508	3.75	95	700	12.54	123
2000.375.0750S	20.00	508	3.75	95	750	13.35	131
22.00 (length in inches) (Silver)							
2200.375.0300S	22.00	559	3.75	95	300	5.40	53
2200.375.0400S	22.00	559	3.75	95	400	7.14	70
2200.375.0500S	22.00	559	3.75	95	500	8.97	88
2200.375.0550S	22.00	559	3.75	95	550	9.79	96
2200.375.0600S	22.00	559	3.75	95	600	10.70	105
2200.375.0700S	22.00	559	3.75	95	700	12.54	123
2200.375.0800S	22.00	559	3.75	95	800	14.27	140
24.00 (length in inches) (Silver)							
2400.375.0300S	24.00	610	3.75	95	300	5.40	53
2400.375.0350S	24.00	610	3.75	95	350	6.22	61
2400.375.0400S	24.00	610	3.75	95	400	7.14	70
2400.375.0450S	24.00	610	3.75	95	450	8.05	79
2400.375.0500S	24.00	610	3.75	95	500	8.97	88
2400.375.0550S	24.00	610	3.75	95	550	9.79	96
2400.375.0600S	24.00	610	3.75	95	600	10.70	105
2400.375.0650S	24.00	610	3.75	95	650	11.62	114
2400.375.0700S	24.00	610	3.75	95	700	12.54	123
33.00 (length in inches) (Silver)							
3300.375.0115S	33.00	838	3.75	95	115	2.04	20
3300.375.0130S	33.00	838	3.75	95	130	2.34	23
Helper							
HELPER375	6.07	154	3.75	95	45	0.80	8
Spacer (ID locating main to helper/tender coupling spacer)							
SPACER375			3.75	95			

Conventional Front

Part Number	Length		Outside Diameter		Rate	
	inch	mm	inch	mm	lbs/inch	N/mm
8.75 (length in inches) - 5.75" O.D.						
0875.575.0300	8.75	222	5.75	146	300	53
0875.575.0325	8.75	222	5.75	146	325	57
0875.575.0350	8.75	222	5.75	146	350	61
0875.575.0375	8.75	222	5.75	146	375	66
0875.575.0400	8.75	222	5.75	146	400	70
0875.575.0425	8.75	222	5.75	146	425	74
0875.575.0450	8.75	222	5.75	146	450	79
0875.575.0460	8.75	222	5.75	146	460	81
0875.575.0475	8.75	222	5.75	146	475	83
0875.575.0500	8.75	222	5.75	146	500	88
0875.575.0525	8.75	222	5.75	146	525	92
0875.575.0550	8.75	222	5.75	146	550	96
0875.575.0575	8.75	222	5.75	146	575	101
0875.575.0600	8.75	222	5.75	146	600	105
0875.575.0625	8.75	222	5.75	146	625	109
0875.575.0650	8.75	222	5.75	146	650	114
0875.575.0675	8.75	222	5.75	146	675	118
0875.575.0700	8.75	222	5.75	146	700	123
0875.575.0750	8.75	222	5.75	146	750	131
0875.575.0800	8.75	222	5.75	146	800	140
0875.575.0825	8.75	222	5.75	146	825	144
0875.575.0850	8.75	222	5.75	146	850	149
0875.575.0875	8.75	222	5.75	146	875	153
0875.575.0900	8.75	222	5.75	146	900	158
0875.575.0925	8.75	222	5.75	146	925	162
0875.575.0950	8.75	222	5.75	146	950	166
0875.575.0975	8.75	222	5.75	146	975	171
0875.575.1000	8.75	222	5.75	146	1,000	175
0875.575.1025	8.75	222	5.75	146	1,025	179
0875.575.1050	8.75	222	5.75	146	1,050	184
0875.575.1100	8.75	222	5.75	146	1,100	193
0875.575.1150	8.75	222	5.75	146	1,150	201
0875.575.1200	8.75	222	5.75	146	1,200	210
0875.575.1225	8.75	222	5.75	146	1,225	214
0875.575.1250	8.75	222	5.75	146	1,250	219
0875.575.1300	8.75	222	5.75	146	1,300	228
0875.575.1325	8.75	222	5.75	146	1,325	232
0875.575.1350	8.75	222	5.75	146	1,350	236
0875.575.1400	8.75	222	5.75	146	1,400	245
0875.575.1450	8.75	222	5.75	146	1,450	254
0875.575.1500	8.75	222	5.75	146	1,500	263
0875.575.1525	8.75	222	5.75	146	1,525	267
0875.575.1550	8.75	222	5.75	146	1,550	271
0875.575.1600	8.75	222	5.75	146	1,600	280
0875.575.1650	8.75	222	5.75	146	1,650	289
0875.575.1700	8.75	222	5.75	146	1,700	298
0875.575.1750	8.75	222	5.75	146	1,750	306
0875.575.1800	8.75	222	5.75	146	1,800	315

Conventional Front



Part Number	Length		Outside Diameter		Rate	
	inch	mm	inch	mm	lbs/inch	N/mm
0875.575.1850	8.75	222	5.75	146	1,850	324
0875.575.1900	8.75	222	5.75	146	1,900	333
0875.575.2000	8.75	222	5.75	146	2,000	350
0875.575.2100	8.75	222	5.75	146	2,100	368
0875.575.2200	8.75	222	5.75	146	2,200	385
0875.575.2300	8.75	222	5.75	146	2,300	403
0875.575.2400	8.75	222	5.75	146	2,400	420
0875.575.2500	8.75	222	5.75	146	2,500	438
0875.575.2600	8.75	222	5.75	146	2,600	455
0875.575.2700	8.75	222	5.75	146	2,700	473
0875.575.2800	8.75	222	5.75	146	2,800	490
9.50 (length in inches) - 5.00" O.D.						
0950.500.0200	9.50	241	5.00	127	200	35
0950.500.0250	9.50	241	5.00	127	250	44
0950.500.0300	9.50	241	5.00	127	300	53
0950.500.0350	9.50	241	5.00	127	350	61
0950.500.0375	9.50	241	5.00	127	375	66
0950.500.0400	9.50	241	5.00	127	400	70
0950.500.0425	9.50	241	5.00	127	400	70
0950.500.0450	9.50	241	5.00	127	450	79
0950.500.0475	9.50	241	5.00	127	475	83
0950.500.0500	9.50	241	5.00	127	500	88
0950.500.0525	9.50	241	5.00	127	525	92
0950.500.0550	9.50	241	5.00	127	550	96
0950.500.0575	9.50	241	5.00	127	575	101
0950.500.0600	9.50	241	5.00	127	600	105
0950.500.0625	9.50	241	5.00	127	625	109
0950.500.0650	9.50	241	5.00	127	650	114
New! 0950.500.0675	9.50	241	5.00	127	675	118
0950.500.0700	9.50	241	5.00	127	700	123
0950.500.0750	9.50	241	5.00	127	750	131
0950.500.0775	9.50	241	5.00	127	775	136
0950.500.0800	9.50	241	5.00	127	800	140
0950.500.0850	9.50	241	5.00	127	850	149
0950.500.0900	9.50	241	5.00	127	900	158
0950.500.0950	9.50	241	5.00	127	950	166
0950.500.1000	9.50	241	5.00	127	1,000	175
0950.500.1050	9.50	241	5.00	127	1,050	184
0950.500.1100	9.50	241	5.00	127	1,100	193
0950.500.1200	9.50	241	5.00	127	1,200	210
0950.500.1250	9.50	241	5.00	127	1,250	219
0950.500.1300	9.50	241	5.00	127	1,300	228
0950.500.1400	9.50	241	5.00	127	1,400	245
0950.500.1500	9.50	241	5.00	127	1,500	263
0950.500.1600	9.50	241	5.00	127	1,600	280
9.50 (length in inches) - 5.50" O.D.						
0950.550.0300	9.50	241	5.50	140	300	53
0950.550.0325	9.50	241	5.50	140	325	57
0950.550.0350	9.50	241	5.50	140	350	61

Conventional Front

Part Number	Length		Outside Diameter		Rate	
	inch	mm	inch	mm	lbs/inch	N/mm
0950.550.0375	9.50	241	5.50	140	375	66
0950.550.0400	9.50	241	5.50	140	400	70
0950.550.0425	9.50	241	5.50	140	425	74
0950.550.0450	9.50	241	5.50	140	450	79
0950.550.0475	9.50	241	5.50	140	475	83
0950.550.0500	9.50	241	5.50	140	500	88
0950.550.0525	9.50	241	5.50	140	525	92
0950.550.0550	9.50	241	5.50	140	550	96
0950.550.0575	9.50	241	5.50	140	575	101
0950.550.0600	9.50	241	5.50	140	600	105
0950.550.0625	9.50	241	5.50	140	625	109
0950.550.0650	9.50	241	5.50	140	650	114
0950.550.0675	9.50	241	5.50	140	675	118
0950.550.0700	9.50	241	5.50	140	700	123
0950.550.0750	9.50	241	5.50	140	750	131
0950.550.0800	9.50	241	5.50	140	800	140
0950.550.0850	9.50	241	5.50	140	850	149
0950.550.0900	9.50	241	5.50	140	900	158
0950.550.0950	9.50	241	5.50	140	950	166
0950.550.1000	9.50	241	5.50	140	1,000	175
0950.550.1050	9.50	241	5.50	140	1,050	184
0950.550.1100	9.50	241	5.50	140	1,100	193
0950.550.1150	9.50	241	5.50	140	1,150	201
0950.550.1200	9.50	241	5.50	140	1,200	210
0950.550.1250	9.50	241	5.50	140	1,250	219
0950.550.1300	9.50	241	5.50	140	1,300	228
0950.550.1350	9.50	241	5.50	140	1,350	236
0950.550.1400	9.50	241	5.50	140	1,400	245
0950.550.1450	9.50	241	5.50	140	1,450	254
0950.550.1500	9.50	241	5.50	140	1,500	263
10.50 (length in inches) - 5.50" O.D.						
1050.550.0300	10.50	267	5.50	140	300	53
1050.550.0325	10.50	267	5.50	140	325	57
1050.550.0350	10.50	267	5.50	140	350	61
1050.550.0375	10.50	267	5.50	140	375	66
1050.550.0400	10.50	267	5.50	140	400	70

Platinum Rear

Platinum Rear - 5.00" O.D.						
ER16.0075	16.00	406	5.00	127	75	13
ER16.0085	16.00	406	5.00	127	85	15
ER16.0100	16.00	406	5.00	127	100	18
ER16.0125	16.00	406	5.00	127	125	22
ER16.0150	16.00	406	5.00	127	150	26
ER16.0175	16.00	406	5.00	127	175	31
ER16.0200	16.00	406	5.00	127	200	35
ER15.0150	15.00	381	5.00	127	150	26
ER15.0175	15.00	381	5.00	127	175	31

Platinum Rear



Part Number	Length		Outside Diameter		Rate	
	inch	mm	inch	mm	lbs/inch	N/mm
ER15.0200	15.00	381	5.00	127	200	35
ER15.0225	15.00	381	5.00	127	225	39
ER15.0250	15.00	381	5.00	127	250	44
New! ER14.0100	14.00	356	5.00	127	100	18
New! ER14.0125	14.00	356	5.00	127	125	22
New! ER14.0150	14.00	356	5.00	127	150	26
ER14.0275	14.00	356	5.00	127	275	48
ER14.0325	14.00	356	5.00	127	325	57
ER14.0375	14.00	356	5.00	127	375	66
ER14.0400	14.00	356	5.00	127	400	70
ER135.0350	13.50	343	5.00	127	350	61
ER13.0300	13.00	330	5.00	127	300	53
ER13.0325	13.00	330	5.00	127	325	57
ER13.0475	13.00	330	5.00	127	475	83
ER13.0500	13.00	330	5.00	127	500	88
ER125.0175	12.50	318	5.00	127	175	31
ER125.0200	12.50	318	5.00	127	200	35
ER125.0225	12.50	318	5.00	127	225	39
ER125.0250	12.50	318	5.00	127	250	44
ER125.0275	12.50	318	5.00	127	275	48
ER125.0300	12.50	318	5.00	127	300	53
ER125.0400	12.50	318	5.00	127	400	70
ER1225.0325	12.25	311	5.00	127	325	57
ER1225.0350	12.25	311	5.00	127	350	61
ER1225.0375	12.25	311	5.00	127	375	66
New! ER12.0400	12.00	305	5.00	127	400	70
ER12.0425	12.00	305	5.00	127	425	74
ER12.0450	12.00	305	5.00	127	450	79
ER12.0475	12.00	305	5.00	127	475	83
ER12.0500	12.00	305	5.00	127	500	88
ER12.0525	12.00	305	5.00	127	525	92
ER12.0550	12.00	305	5.00	127	550	96
ER12.0600	12.00	305	5.00	127	600	105
ER12.0650	12.00	305	5.00	127	650	114
ER115.0700	11.50	292	5.00	127	700	123
ER115.0750	11.50	292	5.00	127	750	131
ER115.0800	11.50	292	5.00	127	800	140
ER115.0850	11.50	292	5.00	127	850	149
ER115.0900	11.50	292	5.00	127	900	158
ER115.0950	11.50	292	5.00	127	950	166
ER115.1000	11.50	292	5.00	127	1,000	175
New! ER1125.0500	11.25	286	5.00	127	500	88
New! ER1125.0550	11.25	286	5.00	127	550	96
New! ER1125.0600	11.25	286	5.00	127	600	105
Max Load Platinum 2,500 lb - 5.00" O.D.						
New! ER2.5K.1125.0300	11.25	286	5.00	127	300	53
New! ER2.5K.1125.0350	11.25	286	5.00	127	350	61
New! ER2.5K.1125.0400	11.25	286	5.00	127	400	70
New! ER2.5K.1125.0450	11.25	286	5.00	127	450	79

Platinum Rear

Part Number	Length		Outside Diameter		Rate	
	inch	mm	inch	mm	lbs/inch	N/mm
New! ER2.5K.1125.0500	11.25	286	5.00	127	500	88
New! ER2.5K.1125.0600	11.25	286	5.00	127	600	105
Max Load Platinum 4,000 lb - 5.00" O.D.						
New! ER4K.1125.0650	11.25	286	5.00	127	650	114
New! ER4K.1125.0700	11.25	286	5.00	127	700	123
New! ER4K.1125.0750	11.25	286	5.00	127	750	131
New! ER4K.1125.0800	11.25	286	5.00	127	800	140
New! ER4K.1125.0850	11.25	286	5.00	127	850	149
New! ER4K.1125.0900	11.25	286	5.00	127	900	158
New! ER4K.1125.0950	11.25	286	5.00	127	950	166
New! ER4K.1125.1000	11.25	286	5.00	127	1,000	175
ER4K.1125.1100	11.25	286	5.00	127	1,100	193
ER4K.1125.1200	11.25	286	5.00	127	1,200	210
ER4K.1125.1300	11.25	286	5.00	127	1,300	228
ER4K.1125.1400	11.25	286	5.00	127	1,400	245
ER4K.1125.1500	11.25	286	5.00	127	1,500	263
Max Load Platinum 5,000 lb - 5.00" O.D.						
New! ER5K.1125.0650	11.25	286	5.00	127	650	114
New! ER5K.1125.0700	11.25	286	5.00	127	700	123
New! ER5K.1125.0750	11.25	286	5.00	127	750	131
New! ER5K.1125.0800	11.25	286	5.00	127	800	140
New! ER5K.1125.0850	11.25	286	5.00	127	850	149
New! ER5K.1125.0900	11.25	286	5.00	127	900	158
New! ER5K.1125.0950	11.25	286	5.00	127	950	166
New! ER5K.1125.1000	11.25	286	5.00	127	1,000	175
New! ER5K.1125.1100	11.25	286	5.00	127	1,100	193
New! ER5K.1125.1200	11.25	286	5.00	127	1,200	210
New! ER5K.1125.1300	11.25	286	5.00	127	1,300	228
New! ER5K.1125.1400	11.25	286	5.00	127	1,400	245
New! ER5K.1125.1500	11.25	286	5.00	127	1,500	263

Conventional Rear

Loaded Height Rear (NASCAR Specs)(700LB @ 10.00")						
LH1.500.0125	15.79	401	5.00	127	125	22
LH1.500.0150	14.88	378	5.00	127	150	26
LH1.500.0175	14.21	361	5.00	127	175	31
LH1.500.0200	13.70	348	5.00	127	200	35
LH1.500.0225	13.31	338	5.00	127	225	39
LH1.500.0250	12.99	330	5.00	127	250	44
LH1.500.0275	12.76	324	5.00	127	275	48
LH1.500.0300	12.52	318	5.00	127	300	53
LH1.500.0325	12.36	314	5.00	127	325	57
LH1.500.0350	12.20	310	5.00	127	350	61
LH1.500.0375	12.05	306	5.00	127	375	66
LH1.500.0400	11.93	303	5.00	127	400	70
LH1.500.0425	11.85	301	5.00	127	425	74
LH1.500.0430	12.01	305	5.00	127	430	75

Conventional Rear



Part Number	Length		Outside Diameter		Rate	
	inch	mm	inch	mm	lbs/inch	N/mm
LH1.500.0450	11.77	299	5.00	127	450	79
LH1.500.0475	11.65	296	5.00	127	475	83
LH1.500.0500	11.61	295	5.00	127	500	88
LH1.500.0525	11.54	293	5.00	127	525	92
LH1.500.0550	11.46	291	5.00	127	550	96
LH1.500.0575	11.42	290	5.00	127	575	101
LH1.500.0600	11.38	289	5.00	127	600	105
LH1.500.0650	11.26	286	5.00	127	650	114
LH1.500.0700	11.18	284	5.00	127	700	123
LH1.500.0750	11.14	283	5.00	127	750	131
LH1.500.0800	11.18	284	5.00	127	800	140
LH1.500.0850	11.14	283	5.00	127	850	149
LH1.500.0900	11.10	282	5.00	127	900	158
LH1.500.0925	11.10	282	5.00	127	925	162
LH1.500.0950	11.10	282	5.00	127	950	166
LH1.500.0975	11.10	282	5.00	127	975	171
LH1.500.1000	11.10	282	5.00	127	1,000	175
LH1.500.1100	11.10	282	5.00	127	1,100	193
LH1.500.1200	11.10	282	5.00	127	1,200	210
LH1.500.1300	11.10	282	5.00	127	1,300	228
LH1.500.1400	11.10	282	5.00	127	1,400	245
11.00 (length in inches) - 5.00" O.D.						
1100.500.0125	11.00	279	5.00	127	125	22
1100.500.0150	11.00	279	5.00	127	150	26
1100.500.0175	11.00	279	5.00	127	175	31
1100.500.0200	11.00	279	5.00	127	200	35
1100.500.0225	11.00	279	5.00	127	225	39
1100.500.0250	11.00	279	5.00	127	250	44
1100.500.0275	11.00	279	5.00	127	275	48
1100.500.0300	11.00	279	5.00	127	300	53
1100.500.0325	11.00	279	5.00	127	325	57
1100.500.0350	11.00	279	5.00	127	350	61
1100.500.0375	11.00	279	5.00	127	375	66
1100.500.0400	11.00	279	5.00	127	400	70
1100.500.0425	11.00	279	5.00	127	425	74
1100.500.0450	11.00	279	5.00	127	450	79
1100.500.0500	11.00	279	5.00	127	500	88
1100.500.0550	11.00	279	5.00	127	550	96
1100.500.0600	11.00	279	5.00	127	600	105
1100.500.0650	11.00	279	5.00	127	650	114
1100.500.0700	11.00	279	5.00	127	700	123
1100.500.0750	11.00	279	5.00	127	750	131
1100.500.0800	11.00	279	5.00	127	800	140
1100.500.0850	11.00	279	5.00	127	850	149
1100.500.0900	11.00	279	5.00	127	900	158
13.00 (length in inches) - 5.00" O.D.						
1300.500.0125	13.00	330	5.00	127	125	22
1300.500.0150	13.00	330	5.00	127	150	26
1300.500.0175	13.00	330	5.00	127	175	31

Conventional Rear

Part Number	Length		Outside Diameter		Rate	
	inch	mm	inch	mm	lbs/inch	N/mm
1300.500.0180	13.00	330	5.00	127	180	32
1300.500.0200	13.00	330	5.00	127	200	35
1300.500.0225	13.00	330	5.00	127	225	39
1300.500.0250	13.00	330	5.00	127	250	44
1300.500.0275	13.00	330	5.00	127	275	48
1300.500.0300	13.00	330	5.00	127	300	53
1300.500.0325	13.00	330	5.00	127	325	57
1300.500.0350	13.00	330	5.00	127	350	61
1300.500.0375	13.00	330	5.00	127	375	66
1300.500.0400	13.00	330	5.00	127	400	70
1300.500.0450	13.00	330	5.00	127	450	79
1300.500.0500	13.00	330	5.00	127	500	88
1300.500.0550	13.00	330	5.00	127	550	96
1300.500.0600	13.00	330	5.00	127	600	105
1300.500.0700	13.00	330	5.00	127	700	123
15.00 (length in inches) - 5.00" O.D.						
1500.500.0125	15.00	381	5.00	127	125	22
1500.500.0150	15.00	381	5.00	127	150	26
1500.500.0165	15.00	381	5.00	127	165	29
1500.500.0175	15.00	381	5.00	127	175	31
1500.500.0200	15.00	381	5.00	127	200	35
1500.500.0225	15.00	381	5.00	127	225	39
1500.500.0250	15.00	381	5.00	127	250	44
1500.500.0275	15.00	381	5.00	127	275	48
1500.500.0300	15.00	381	5.00	127	300	53
16.00 (length in inches) - 5.00" O.D.						
1600.500.0100	16.00	406	5.00	127	100	18
1600.500.0125	16.00	406	5.00	127	125	22
1600.500.0150	16.00	406	5.00	127	150	26
1600.500.0175	16.00	406	5.00	127	175	31
1600.500.0200	16.00	406	5.00	127	200	35
1600.500.0225	16.00	406	5.00	127	225	39
1600.500.0250	16.00	406	5.00	127	250	44

SPRING LOCATOR

Part Number	Inside Diameter (Perch O.D.)		Outside Diameter (Spring I.D.)	
	inch	mm	inch	mm
Spring Locator (I.D = Perch Diameter / O.D. = Spring I.D.)				
ESL350.4125	3.50	89	4.125	105
ESL350.4188	3.50	89	4.188	106
ESL375.4000	3.75	95	4.000	102
ESL375.4063	3.75	95	4.063	103
ESL375.4125	3.75	95	4.125	105
ESL375.4188	3.75	95	4.188	106
ESL375.4313	3.75	95	4.313	110
ESL375.4375	3.75	95	4.375	111

COIL SLEEVE | 5.00" O.D.



	Spring Diameter Range		Spring Wire Diameter Range		Coil Sleeve Length	
	inch	mm	inch	mm	inch	mm
Coil Sleeve (Fits 5.00" O.D. Springs)						
CS5001 (NASCAR Approved)	4.50-6.00	114-152	0.423-0.541	11-14	13.43	341
CS5001L	4.50-6.00	114-152	0.423-0.541	11-14	16.50	419
CS5002 (NASCAR Approved)	4.50-6.00	114-152	0.551-0.650	14-17	13.43	341
CS5002L	4.50-6.00	114-152	0.551-0.650	14-17	16.50	419

SPRING BAGS | 5.00" O.D.

	Quantity	Spring Diameter		Spring Length	
		inch	mm	inch	mm
Protective Spring Bags-Pair (Fits 5.00" O.D. Springs)					
ESB14.500	2	5.00	127	12" - 14"	305-356
ESB16.500	2	5.00	127	14" - 16"	356-406

6TH COIL SPRING | 5.00" O.D.

	Length		Outside Diameter		Rate	
	inch	mm	inch	mm	lbs/inch	N/mm
6th Coil Spring						
New! 0400.500.0400	4.00	102	5.00	127	400	70
New! 0400.500.0450	4.00	102	5.00	127	450	79
New! 0400.500.0500	4.00	102	5.00	127	500	88

SPRING BAGS | 5.00" O.D.

	Quantity	Spring Diameter		Spring Length	
		inch	mm	inch	mm
Protective Spring Bag (Fits 6th Coil Springs)					
New! ESB5.400	1	5.00	127	4.00	102

PULL BAR SPRING | 5.00" O.D.

	Length		Outside Diameter		Rate	
	inch	mm	inch	mm	lbs/inch	N/mm
Pull Bar Spring						
0675.500.1000	6.75	171	5.00	127	500 / 1000	88 / 175
New! 0675.500.1200	6.75	171	5.00	127	600 / 1200	105 / 210
0675.500.1500	6.75	171	5.00	127	750 / 1500	131 / 263
New! 0675.500.2000	6.75	171	5.00	127	600 / 2000	105 / 350
0700.500.0600	7.00	178	5.00	127	600	105
0700.500.0800	7.00	178	5.00	127	800	140

SPRING BAG | 5.00" O.D.

	Quantity	Spring Diameter		Spring Length	
		inch	mm	inch	mm
Protective Spring Bag (Fits Pull Bar Springs)					
New! ESB875.500	1	5.00	127	8.75	222

Part Number	Length		Inside Diameter		Rate	
	mm	inch	mm	inch	N/m	lbs/inch
80 (length in mm)						
80-60-0100	80	3.15	60	2.36	100	571
80-60-0120	80	3.15	60	2.36	120	685
80-60-0140	80	3.15	60	2.36	140	800
80-60-0160	80	3.15	60	2.36	160	914
80-60-0180	80	3.15	60	2.36	180	1,028
80-60-0200	80	3.15	60	2.36	200	1,142
80-60-0220	80	3.15	60	2.36	220	1,256
80-60-0240	80	3.15	60	2.36	240	1,371
80-60-0260	80	3.15	60	2.36	260	1,485
80-60-0280	80	3.15	60	2.36	280	1,599
80-60-0300	80	3.15	60	2.36	300	1,713
100 (length in mm)						
100-60-0070	100	3.94	60	2.36	70	400
100-60-0080	100	3.94	60	2.36	80	457
100-60-0090	100	3.94	60	2.36	90	514
100-60-0100	100	3.94	60	2.36	100	571
100-60-0110	100	3.94	60	2.36	110	628
100-60-0120	100	3.94	60	2.36	120	685
100-60-0140	100	3.94	60	2.36	140	800
100-60-0160	100	3.94	60	2.36	160	914
100-60-0180	100	3.94	60	2.36	180	1,028
100-60-0200	100	3.94	60	2.36	200	1,142
100-60-0220	100	3.94	60	2.36	220	1,256
100-60-0240	100	3.94	60	2.36	240	1,371
100-60-0260	100	3.94	60	2.36	260	1,485
100-60-0280	100	3.94	60	2.36	280	1,599
100-60-0300	100	3.94	60	2.36	300	1,713
100-60-0320	100	3.94	60	2.36	320	1,828
100-60-0340	100	3.94	60	2.36	340	1,942
100-60-0360	100	3.94	60	2.36	360	2,056
100-60-0380	100	3.94	60	2.36	380	2,170
100-60-0400	100	3.94	60	2.36	400	2,284
100-60-0450	100	3.94	60	2.36	450	2,570
100-60-0500	100	3.94	60	2.36	500	2,856
100-60-0550	100	3.94	60	2.36	550	3,141
100-60-0600	100	3.94	60	2.36	600	3,427
100-60-0650	100	3.94	60	2.36	650	3,712
100-60-0700	100	3.94	60	2.36	700	3,998
100-60-0750	100	3.94	60	2.36	750	4,283
100-60-0800	100	3.94	60	2.36	800	4,569
120 (length in mm)						
120-60-0040	120	4.72	60	2.36	40	228
120-60-0050	120	4.72	60	2.36	50	286
120-60-0060	120	4.72	60	2.36	60	343
120-60-0070	120	4.72	60	2.36	70	400
120-60-0080	120	4.72	60	2.36	80	457
120-60-0090	120	4.72	60	2.36	90	514
120-60-0100	120	4.72	60	2.36	100	571
120-60-0110	120	4.72	60	2.36	110	628
120-60-0120	120	4.72	60	2.36	120	685
120-60-0140	120	4.72	60	2.36	140	800

Part Number	Length		Inside Diameter		Rate	
	mm	inch	mm	inch	N/m	lbs/inch
120-60-0160	120	4.72	60	2.36	160	914
120-60-0180	120	4.72	60	2.36	180	1,028
120-60-0200	120	4.72	60	2.36	200	1,142
120-60-0220	120	4.72	60	2.36	220	1,256
120-60-0240	120	4.72	60	2.36	240	1,371
120-60-0260	120	4.72	60	2.36	260	1,485
120-60-0280	120	4.72	60	2.36	280	1,599
120-60-0300	120	4.72	60	2.36	300	1,713
120-60-0320	120	4.72	60	2.36	320	1,828
120-60-0340	120	4.72	60	2.36	340	1,942
120-60-0360	120	4.72	60	2.36	360	2,056
140 (length in mm)						
140-60-0050	140	5.51	60	2.36	50	286
140-60-0060	140	5.51	60	2.36	60	343
140-60-0070	140	5.51	60	2.36	70	400
140-60-0080	140	5.51	60	2.36	80	457
140-60-0090	140	5.51	60	2.36	90	514
140-60-0100	140	5.51	60	2.36	100	571
140-60-0110	140	5.51	60	2.36	110	628
140-60-0120	140	5.51	60	2.36	120	685
140-60-0130	140	5.51	60	2.36	130	742
140-60-0140	140	5.51	60	2.36	140	800
140-60-0150	140	5.51	60	2.36	150	857
140-60-0160	140	5.51	60	2.36	160	914
140-60-0170	140	5.51	60	2.36	170	971
140-60-0180	140	5.51	60	2.36	180	1,028
140-60-0190	140	5.51	60	2.36	190	1,085
140-60-0200	140	5.51	60	2.36	200	1,142
140-60-0220	140	5.51	60	2.36	220	1,256
140-60-0240	140	5.51	60	2.36	240	1,371
140-60-0260	140	5.51	60	2.36	260	1,485
140-60-0280	140	5.51	60	2.36	280	1,599
140-60-0300	140	5.51	60	2.36	300	1,713
140-60-0350	140	5.51	60	2.36	350	1,999
140-60-0400	140	5.51	60	2.36	400	2,284
140-60-0450	140	5.51	60	2.36	450	2,570
140-60-0500	140	5.51	60	2.36	500	2,856
170 (length in mm)						
170-60-0030	170	6.69	60	2.36	30	171
170-60-0040	170	6.69	60	2.36	40	228
170-60-0050	170	6.69	60	2.36	50	286
170-60-0060	170	6.69	60	2.36	60	343
170-60-0070	170	6.69	60	2.36	70	400
170-60-0080	170	6.69	60	2.36	80	457
170-60-0090	170	6.69	60	2.36	90	514
170-60-0100	170	6.69	60	2.36	100	571
170-60-0110	170	6.69	60	2.36	110	628
170-60-0120	170	6.69	60	2.36	120	685
170-60-0130	170	6.69	60	2.36	130	742
170-60-0140	170	6.69	60	2.36	140	800
170-60-0150	170	6.69	60	2.36	150	857
170-60-0160	170	6.69	60	2.36	160	914

Part Number	Length		Inside Diameter		Rate	
	mm	inch	mm	inch	N/m	lbs/inch
170-60-0170	170	6.69	60	2.36	170	971
170-60-0180	170	6.69	60	2.36	180	1,028
170-60-0190	170	6.69	60	2.36	190	1,085
170-60-0200	170	6.69	60	2.36	200	1,142
170-60-0220	170	6.69	60	2.36	220	1,256
170-60-0240	170	6.69	60	2.36	240	1,371
170-60-0260	170	6.69	60	2.36	260	1,485
170-60-0280	170	6.69	60	2.36	280	1,599
170-60-0300	170	6.69	60	2.36	300	1,713
180 (length in mm)						
180-60-0040	180	7.09	60	2.36	40	228
180-60-0050	180	7.09	60	2.36	50	286
180-60-0060	180	7.09	60	2.36	60	343
180-60-0140	180	7.09	60	2.36	140	800
180-60-0150	180	7.09	60	2.36	150	857
180-60-0170	180	7.09	60	2.36	170	971
180-60-0200	180	7.09	60	2.36	200	1,142
200 (length in mm)						
200-60-0030	200	7.87	60	2.36	30	171
200-60-0040	200	7.87	60	2.36	40	228
200-60-0050	200	7.87	60	2.36	50	286
200-60-0060	200	7.87	60	2.36	60	343
200-60-0070	200	7.87	60	2.36	70	400
200-60-0080	200	7.87	60	2.36	80	457
200-60-0090	200	7.87	60	2.36	90	514
200-60-0100	200	7.87	60	2.36	100	571
200-60-0110	200	7.87	60	2.36	110	628
200-60-0120	200	7.87	60	2.36	120	685
250 (length in mm)						
250-60-0025	250	9.84	60	2.36	25	143
250-60-0030	250	9.84	60	2.36	30	171
250-60-0035	250	9.84	60	2.36	35	200
250-60-0040	250	9.84	60	2.36	40	228
250-60-0045	250	9.84	60	2.36	45	257
250-60-0050	250	9.84	60	2.36	50	286
250-60-0060	250	9.84	60	2.36	60	343
250-60-0070	250	9.84	60	2.36	70	400
250-60-0080	250	9.84	60	2.36	80	457
250-60-0090	250	9.84	60	2.36	90	514
250-60-0100	250	9.84	60	2.36	100	571
250-60-0110	250	9.84	60	2.36	110	628
250-60-0120	250	9.84	60	2.36	120	685
300 (length in mm)						
300-60-0020	300	11.81	60	2.36	20	114
300-60-0025	300	11.81	60	2.36	25	143
300-60-0030	300	11.81	60	2.36	30	171
300-60-0035	300	11.81	60	2.36	35	200
300-60-0040	300	11.81	60	2.36	40	228
300-60-0045	300	11.81	60	2.36	45	257
300-60-0050	300	11.81	60	2.36	50	286
300-60-0060	300	11.81	60	2.36	60	343

Part Number	Length		Inside Diameter		Rate	
	mm	inch	mm	inch	N/m	lbs/inch
300-60-0070	300	11.81	60	2.36	70	400
300-60-0080	300	11.81	60	2.36	80	457
300-60-0090	300	11.81	60	2.36	90	514
300-60-0100	300	11.81	60	2.36	100	571
350 (length in mm)						
350-60-0020	350	13.78	60	2.36	20	114
350-60-0025	350	13.78	60	2.36	25	143
350-60-0030	350	13.78	60	2.36	30	171
350-60-0035	350	13.78	60	2.36	35	200
350-60-0040	350	13.78	60	2.36	40	228
350-60-0045	350	13.78	60	2.36	45	257
350-60-0050	350	13.78	60	2.36	50	286
350-60-0055	350	13.78	60	2.36	55	314
Tender/Linear						
30-60-0120	70	2.76	60	2.36	120	685
35-60-0065	60	2.36	60	2.36	65	371
40-60-0020	55	2.17	60	2.36	20	114
40-60-0030	65	2.56	60	2.36	30	171
40-60-0040	75	2.95	60	2.36	40	228
40-60-0050	68	2.68	60	2.36	50	286
40-60-0055	68	2.68	60	2.36	55	314
40-60-0060	66	2.60	60	2.36	60	343
40-60-0070	65	2.56	60	2.36	70	400
40-60-0120	80	3.15	60	2.36	120	685
50-60-0020	78	3.07	60	2.36	20	114
50-60-0030	90	3.54	60	2.36	30	171
50-60-0065	82	3.23	60	2.36	65	371
50-60-0120	90	3.54	60	2.36	120	685
60-60-0030	101	3.98	60	2.36	30	171
60-60-0040	113	4.45	60	2.36	40	228
60-60-0050	105	4.13	60	2.36	50	286
60-60-0060	96	3.78	60	2.36	60	343
60-60-0070	95	3.74	60	2.36	70	400
70-60-0030	108	4.25	60	2.36	30	171
Tender/Progressive						
50-60-0040/0120	106	4.17	60	2.36	40 / 120	228 / 385
50-60-0060/0150	117	4.61	60	2.36	60 / 150	343 / 857
Helper						
60-60-0002	75	2.87	60	2.36	2	11
80-60-0010	104	4.09	60	2.36	10	57
100-60-0010	124	4.88	60	2.36	10	57
Hardware						
1-60-00 (Spring Coupler)						
Adapter						
ADAPTER60-250 (Perch Adapter 60mm to 2.50")			60 / 2.50	60 / 64		

COILOVER | 70mm I.D.

Part Number	Length		Inside Diameter		Rate	
	mm	inch	mm	inch	N/m	lbs/inch
200 (length in mm)						
200-70-0050	200	7.87	70	2.76	50	286
200-70-0055	200	7.87	70	2.76	55	314
200-70-0060	200	7.87	70	2.76	60	343
200-70-0065	200	7.87	70	2.76	65	371
200-70-0070	200	7.87	70	2.76	70	400
200-70-0075	200	7.87	70	2.76	75	428
200-70-0080	200	7.87	70	2.76	80	457
200-70-0085	200	7.87	70	2.76	85	485
200-70-0090	200	7.87	70	2.76	90	514
200-70-0100	200	7.87	70	2.76	100	571
200-70-0110	200	7.87	70	2.76	110	628
200-70-0120	200	7.87	70	2.76	120	685
225 (length in mm)						
225-70-0050	225	8.86	70	2.76	50	286
225-70-0055	225	8.86	70	2.76	55	314
225-70-0060	225	8.86	70	2.76	60	343
225-70-0065	225	8.86	70	2.76	65	371
225-70-0070	225	8.86	70	2.76	70	400
225-70-0075	225	8.86	70	2.76	75	428
225-70-0080	225	8.86	70	2.76	80	457
225-70-0085	225	8.86	70	2.76	85	485
225-70-0090	225	8.86	70	2.76	90	514
225-70-0100	225	8.86	70	2.76	100	571
225-70-0110	225	8.86	70	2.76	110	628
225-70-0120	225	8.86	70	2.76	120	685
250 (length in mm)						
250-70-0040	250	9.84	70	2.76	40	228
250-70-0045	250	9.84	70	2.76	45	257
250-70-0050	250	9.84	70	2.76	50	286
250-70-0055	250	9.84	70	2.76	55	314
250-70-0060	250	9.84	70	2.76	60	343
250-70-0065	250	9.84	70	2.76	65	371
250-70-0070	250	9.84	70	2.76	70	400
250-70-0075	250	9.84	70	2.76	75	428
250-70-0080	250	9.84	70	2.76	80	457
250-70-0085	250	9.84	70	2.76	85	485
250-70-0090	250	9.84	70	2.76	90	514
250-70-0100	250	9.84	70	2.76	100	571
250-70-0110	250	9.84	70	2.76	110	628
250-70-0120	250	9.84	70	2.76	120	685
300 (length in mm)						
300-70-0020	300	11.81	70	2.76	20	114
300-70-0025	300	11.81	70	2.76	25	143
300-70-0030	300	11.81	70	2.76	30	171
300-70-0035	300	11.81	70	2.76	35	200
300-70-0040	300	11.81	70	2.76	40	228
300-70-0045	300	11.81	70	2.76	45	257
300-70-0050	300	11.81	70	2.76	50	286
300-70-0055	300	11.81	70	2.76	55	314
300-70-0060	300	11.81	70	2.76	60	343

COILOVER | 70mm I.D.



Part Number	Length		Inside Diameter		Rate	
	mm	inch	mm	inch	N/m	lbs/inch
350 (length in mm)						
350-70-0020	350	13.78	70	2.76	20	114
350-70-0025	350	13.78	70	2.76	25	143
350-70-0030	350	13.78	70	2.76	30	171
350-70-0035	350	13.78	70	2.76	35	200
350-70-0040	350	13.78	70	2.76	40	228
350-70-0045	350	13.78	70	2.76	45	257
350-70-0050	350	13.78	70	2.76	50	286
350-70-0055	350	13.78	70	2.76	55	314
350-70-0060	350	13.78	70	2.76	60	343
Tender/Linear						
40-70-0030	82	3.23	70	2.76	30	171
40-70-0040	78	3.07	70	2.76	40	228
40-70-0060	71	2.80	70	2.76	60	343
60-70-0045	98	3.86	70	2.76	45	257
70-70-0015	97	3.82	70	2.76	15	86
70-70-0030	118	4.65	70	2.76	30	171
70-70-0034	108	4.25	70	2.76	34	194
70-70-0038	111	4.37	70	2.76	38	217
70-70-0042	111	4.37	70	2.76	42	240
70-70-0046	106	4.17	70	2.76	46	263
70-70-0050	121	4.76	70	2.76	50	286
70-70-0060	121	4.76	70	2.76	60	343
Helper						
80-70-0003	93	3.66	70	2.76	3	17
Hardware						
1-70-00 (Spring Coupler)						



F3 | Standard

Part Number	Length		Inside Diameter		Rate	
	mm	inch	mm	inch	N/m	lbs/inch
F3 Standard						
F3 C400	141	5.55	36	1.42	70	400
F3 C450	139	5.47	36	1.42	79	451
F3 C500	136	5.35	36	1.42	88	503
F3 C550	134	5.28	36	1.42	96	548
F3 C600	133	5.24	36	1.42	105	600
F3 C700	130	5.12	36	1.42	123	702
F3 C800	128	5.04	36	1.42	140	800
F3 C900	127	5.00	36	1.42	158	902
F3 C1000	126	4.96	36	1.42	175	999
F3 C1100	125	4.92	36	1.42	193	1,102
F3 C1200	124	4.88	36	1.42	210	1,199
F3 C1300	123	4.84	36	1.42	228	1,302
F3 C1400	123	4.84	36	1.42	245	1,399
F3 C1500	122	4.80	36	1.42	263	1,502
F3 C1600	122	4.80	36	1.42	280	1,599
F3 C1800	121	4.76	36	1.42	315	1,799
F3 C2000	121	4.76	36	1.42	350	1,999

F3 | Short

F3 Short						
40494	111	4.37	36	1.42	105	600
40495	103	4.06	36	1.42	114	651
40496	97	3.82	36	1.42	123	702
40497	91	3.58	36	1.42	131	748
40498	86	3.39	36	1.42	140	800
40499	82	3.23	36	1.42	149	851
40500	78	3.07	36	1.42	158	902
40501	74	2.91	36	1.42	166	948
40502	71	2.80	36	1.42	175	999
40503	68	2.68	36	1.42	184	1,051
40504	66	2.60	36	1.42	193	1,102
54587	63	2.48	36	1.42	201	1,148
54588	61	2.40	36	1.42	210	1,199
54589	59	2.32	36	1.42	219	1,251
54590	58	2.28	36	1.42	228	1,302





Your Eibach Partner:

USA

Eibach Springs, Inc.
264 Mariah Circle
Corona, CA 92879-1751
Phone +1 951 256 - 83 00
Fax +1 951 256 - 83 33
E-mail eibach@eibach.com

Germany

Heinrich Eibach GmbH
Am Lennedamm 1
57413 Finnentrop
Phone +49 27 21 - 5 11-342
Fax +49 27 21 - 5 11-111
E-mail eibach@eibach.de

Australia

Eibach Suspension Technology P.T.Y. Ltd.
3/4 Prosperity Parade
Warriewood NSW 2102
Phone +61 2-99 99-36 55
Fax +61 2-99 99-38 55
E-mail eibach@eibach.com.au

China

Eibach Springs (Taicang) Ltd.
No. 63 Ningbo Road
Taicang, Jiangsu
China, 215400
Phone +86 512 53 59 23 88
Fax +86 512 53 59 23 89
E-mail eibach@eibach-china.com

Japan

Eibach Japan Co., Ltd.
No. 3-9-36 Yuigahama
Kanagawa-Pref.
Kamakura-City 248-0014
Japan
Phone +81 4 67 61 - 36 10
Fax +81 4 67 61 - 36 15
E-mail eibach@eibach.jp

South Africa

Eibach South Africa P.T.Y. Ltd.
P.O. Box 2495
North End 6045
Port Elizabeth
Phone +27 41 - 4 51 53 11
Fax +27 41 - 4 53 42 74
E-mail eibachsa@telkomsa.net

United Kingdom

Eibach UK
25, Swannington Road
Broughton Astley
Leicestershire LE9 6TU
Phone +44 14 55 - 28 58 51
Fax +44 14 55 - 28 58 53
E-mail sales@eibach.co.uk

